

Industrial Lighting

Designing your lighting solutions



Contents

Low Glare Battens



Weston Batten
019-020



Upton Batten
021-022



Kingston Batten
023-024



Hilton Batten
025-026



Kaston Batten
027-028



Sutton Batten
029-030

Linear Light



Marco linear
033-038



Polo suspend linear
039-042

Batten Light



T8 Slim Batten
045-046



Narrow Slim Batten
047



Frosted Slim Batten
048



Upton Frosted | 80mm
049



Kingston Frosted | 120mm
050



Hilton Frosted | 150mm
051



Kaston Frosted | 200mm
052



Wega Batten
053



General Batten
054



TX Batten
055



Grid Batten
056



Arco Batten
057-058



Recessed Batten
059



Recessed Frosted
060

Retro Flex Fitting



Retro Flex | Honeycomb
063-066



Retro Flex | PC
063-066



Retro Flex | Lens
063-066

Contents

Pro-Line



Gentle Module
067-072



Frosted Module
067-072



Lens Module
067-072



Narrow Module
067-072



T8 Module
067-072

Asymmetric Light



Fasco Asymmetric Light
075



Dasco Asymmetric Light
076



Track Asymmetric Light
077-078

Tri-Proof Light



Prime Tri-proof | TR100
081-082



Deco Tri-proof | TR200
083-084



Deco S Tri-proof | TR200
085-086



Basic Tri-proof | TR300
087



Tubar Light | TR400
088



Single NCF | TR500
089-090



Twins NCF | TR510
091-092

LED Bulkheads



MOD
095-100



Gamma
101-104



Pro R
105-107



Pro RA
108



Pro S
109



Pro SA
110



Lunar
111-114



Astro
115-118

Contents

LED Bulkheads



Delta
119-120



Wall Pack
121-122



Wall Pack
123-124

Ceiling Light



Vasco R350A
127-128



Vasco R450A
129



Vasco R600A
130



Vasco R900A
131-132



LEO R355A
133-134



LEO R435A
135-136

Panel Light



Backlit Panel
139-145



Edgelit Panel
147-152



Air Handling Panel
153-154



Upscale Panel
155-156

LED Down Light



EVO Down Light
DL100
159



Slim Down Light
DL200
160



Halo Down Light
DL300
161



Halo Down Light
DL400
162

LED Tube



T8 LED Tube
165



T6 LED Tube
166



Cabinet Light
167-168

Product Guide

Product category/name

Product picture

Certificate symbols

Dimension drawing

Product profile

Key features/
selling points

Options

Options for CCT/function/
electrical/photometric/
wiring/IP rating/finish, etc

Order code

These unique codes relate
to individual product
specification

Package information for container

Weston Batten
Low glare | 55mm

SAA CE UK CA

Features

- > Low glare UGR<22
- > End or rear cable entry
- > Single or multiple link
- > 5 years warranty

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
BT02-10KN1-SWNI-E-001	10W	typ.1200	typ.120	Y	L605 X W55 X H63.5	6.0kg	8pcs
BT04-17KN1-SWNI-E-001	17W	typ.2040	typ.120	Y	L1205 X W55 X H63.5	11.5kg	8pcs
BT04-30KN1-SWNI-E-001	34W	typ.4280	typ.120	Y	L1205 X W55 X H63.5	11.5kg	8pcs
BT05-22KN1-SWNI-E-001	22W	typ.2640	typ.120	Y	L1205 X W55 X H63.5	11.5kg	8pcs
BT05-40KN1-SWNI-E-001	40W	typ.4800	typ.120	Y	L1205 X W55 X H63.5	14.5kg	8pcs
BT06-27KN1-SWNI-E-001	27W	typ.3240	typ.120	Y	L1205 X W55 X H63.5	14.5kg	8pcs
BT06-50KN1-SWNI-E-001	50W	typ.6000	typ.120	Y	L1805 X W55 X H63.5	17.0kg	8pcs

Contents

UFO Highbay



REVO UFO | HB100
■ 171-172



Elite UFO | HB200
■ 173-174



Mate UFO | HB400
■ 175-176



Mate UFO | HB420
■ 177



Mate UFO | HB430
■ 178

Linear Highbay



T-line
HB500
■ 182



T-line
HB520
■ 183



T-line
HB540
■ 184



Modular Highbay
HB600 | 3x100W- (60cm)
■ 187



Modular Highbay
HB602 | 3x150W- (90cm)
■ 188



Modular Highbay
HB604 | 3x200W- (120cm)
■ 189

Product Guide

Product category/name

Product picture

Certificate symbols

Dimension drawing

Product profile

Key features/
selling points

Options

Order code

Package information for container

T-line
Linear Highbay

Asymmetric Honeycomb | 160lm/w

The asymmetric honeycomb T-Line Linear Highbay was designed to offer maximum efficacy, a long lifespan, glare protection, and a wide range of features.

The unique and modern appearance heatsink design assures excellent heat dissipation for up to 200W and up to 160lm/w system efficacy with 5 years warranty. The special asymmetric Honeycomb Reflectors reduce glare with special supermarket applications.

Features

- > Highly energy efficacy - up to 160 lm/w
- > Asymmetric Honeycomb reflector for 60°/90° degree heat dissipation
- > Superior honeycomb-reflector-optic for excellent Applications
- > Newest generation of SMD2835 1W LED chips
- > No UV or IR and completely mercury free
- > Various end cap colors available
- > L80/B10 @ 50,000h & 5 years warranty

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
HB02-1ATN1-TSNGS-001	100W	typ.16000	typ.160	Y	L623 X W138 X H73	5.8kg	1pcs
HB03-1CTN1-TSNGS-001	120W	typ.19200	typ.160	Y	L923 X W138 X H73	7.8kg	1pcs
HB03-1BTN1-TSNGS-001	150W	typ.24000	typ.160	Y	L923 X W138 X H73	7.8kg	1pcs
HB04-2ATN1-TSNGS-001	200W	typ.32000	typ.160	Y	L1223 X W138 X H73	10.0kg	1pcs

CCT Single Color 3000K-4000K-5000K-6000K

Function

Electrical Parameters


Photometric Parameters

IP/IK

Options for CCT/function/
electrical/photometric/
wiring/IP rating/finish, etc


These unique codes relate
to individual product
specification

Package information for container



Weston Batten

BT100 | 55mm




Weston is 55mm low glare linear which were widely used in the office /commercial / industrial / education applications. Aluminum case is a excellent heating sink, the high technology SMD2835 provide a more higher lumen output.

► Features

- > Low glare UGR<22
- > End or rear cable entry
- > Single or multiple link
- > 5 years warranty

► CCT



► Function



► Electrical Parameters



► Photometric Parameters




► Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
BT100-02W-KN1-10F01-00	10W	typ.1200	typ.120	Y	L605 X W55 X H63.5	6.0kg	8pcs
BT100-04W-KN1-17F01-00	17W	typ.2040	typ.120	Y	L1205 X W55 X H63.5	11.5kg	8pcs
BT100-04W-KN1-34F01-00	34W	typ.4080	typ.120	Y	L1205 X W55 X H63.5	11.5kg	8pcs
BT100-05W-KN1-28F01-00	28W	typ.2640	typ.120	Y	L1505 X W55 X H63.5	14.5kg	8pcs
BT100-05W-KN1-40F01-00	40W	typ.4800	typ.120	Y	L1505 X W55 X H63.5	14.5kg	8pcs
BT100-06W-KN1-31F01-00	31W	typ.3720	typ.120	Y	L1805 X W55 X H63.5	17.0kg	8pcs
BT100-06W-KN1-62F01-00	62W	typ.7440	typ.120	Y	L1805 X W55 X H63.5	17.0kg	8pcs




Finish





Upton Batten

BT110 | 80mm




Upton Batten is 80mm low glare linear which were widely used on the office / commercial / industrial / education applications. Aluminum case is a excellent heating sink, the high technology SMD2835 provide a more higher lumen output.

Features

- > Low glare UGR<19
- > End or rear cable entry
- > Single or multiple link
- > 5 years warranty

► CCT



► Function



► Electrical Parameters



► Photometric Parameters



Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
BT110-02W-KN1-10F01-00	10W	typ.1200	typ.120	Y	L600 X W80 X H63.5	7.0kg	6pcs
BT110-04W-KN1-17F01-00	17W	typ.2040	typ.120	Y	L1200 X W80 X H63.5	12.0kg	6pcs
BT110-04W-KN1-34F01-00	34W	typ.4080	typ.120	Y	L1200 X W80 X H63.5	12.0kg	6pcs
BT110-05W-KN1-22F01-00	22W	typ.2640	typ.120	Y	L1500 X W80 X H63.5	14.0kg	6pcs
BT110-05W-KN1-40F01-00	40W	typ.4800	typ.120	Y	L1500 X W80 X H63.5	14.0kg	6pcs
BT110-06W-KN1-27F01-00	27W	typ.3240	typ.120	Y	L1800 X W80 X H63.5	18.0kg	6pcs
BT110-06W-KN1-50F01-00	50W	typ.6000	typ.120	Y	L1800 X W80 X H63.5	18.0kg	6pcs



Finish




Upton Batten



Kingston Batten

BT120 | 120mm




Kingston batten is a 120mm low glare batten with UGR<19. It was widely used on the office /commercial / industrial / education applications. Aluminum case is a excellent heating sink, the high technology SMD2835 provide a more higher lumen output.

Features

- > Low glare UGR<19
- > End or rear cable entry
- > Single or multiple link
- > 5 years warranty

CCT



Function



Electrical Parameters



Photometric Parameters



Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
BT120-02W-KN1-10F01-00	10W	typ.1200	typ.120	Y	L600 X W120 X H63.5	7.0kg	4pcs
BT120-04W-KN1-17F01-00	17W	typ.2040	typ.120	Y	L1200 X W120 X H63.5	10.5kg	4pcs
BT120-04W-KN1-34F01-00	34W	typ.4080	typ.120	Y	L1200 X W120 X H63.5	10.5kg	4pcs
BT120-04W-KN1-22F01-00	22W	typ.2640	typ.120	Y	L1500 X W120 X H63.5	13.0kg	4pcs
BT120-05W-KN1-40F01-00	40W	typ.4800	typ.120	Y	L1500 X W120 X H63.5	13.0kg	4pcs
BT120-06W-KN1-27F01-00	27W	typ.3240	typ.120	Y	L1800 X W120 X H63.5	15.5kg	4pcs
BT120-06W-KN1-50F01-00	50W	typ.6000	typ.120	Y	L1800 X W120 X H63.5	15.5kg	4pcs



Finish _____






Hilton Batten




Finish



Hilton Batten

BT130 | 150mm



HiltonBatten is a 150mm low glare linear which were widely used on the office /commerical / industrial / education applications. Aluminum case is a excellent heating sink, the high technology SMD2835 provide a more higher lumen output.


Features

- > Low glare UGR<19
- > End or rear cable entry
- > Single or multiple link
- > 5 years warranty

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
BT130-04W-KN1-25F01-00	25W	typ.3100	typ.125	Y	L1200 X W150 X H64	18.5kg	3pcs
BT130-04W-KN1-40F01-00	40W	typ.5000	typ.125	Y	L1200 X W150 X H64	18.5kg	3pcs
BT130-05W-KN1-45F01-00	45W	typ.5600	typ.125	Y	L1500 X W150 X H64	22.0kg	3pcs
BT130-05W-KN1-60F01-00	60W	typ.7500	typ.125	Y	L1500 X W150 X H64	22.0kg	3pcs

CCT



Function



Electrical Parameters




Photometric Parameters





Kaston Batten

BT140 | 200mm



Kaston batten is a 200mm low glare linear which were widely used on the office /commerical / industrial / education applications. Aluminum case is a excellent heating sink, the high technology SMD2835 provide a more higher lumen output.


Features

- > Low glare UGR<19
- > End or rear cable entry
- > Single or multiple link
- > 5 years warranty

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
BT140-04W-KN1-25F01-00	25W	typ.3100	typ.125	Y	L1200 X W200 X H64	18.5kg	3pcs
BT140-04W-KN1-40F01-00	40W	typ.5000	typ.125	Y	L1200 X W200 X H64	18.5kg	3pcs
BT140-05W-KN1-45F01-00	45W	typ.5600	typ.125	Y	L1500 X W200 X H64	22.0kg	3pcs
BT140-05W-KN1-60F01-00	60W	typ.7500	typ.125	Y	L1500 X W200 X H64	22.0kg	3pcs

CCT



Function



Electrical Parameters



Photometric Parameters




Finish _____





Sutton Batten

BT160 | 200mm



Sutton batten is a 200mm steel low glare linear with various of functions, The insert inner unit makes the sutton batten easy on the installation and replacement . Sutton batten were widely used on the commercial / industrial /office and campus applications


► Features

- > Low glare UGR<19
- > End or rear cable entry
- > Single or multiple link
- > 5 years warranty

► Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
BT160-04W-PN1-40F01-00	40W	typ.5600	typ.140	Y	L1170X W170 X H30	22.0kg	4pcs
BT160-05W-PN1-60F01-00	60W	typ.8400	typ.140	Y	L1470 X W170 X H30	25.0kg	4pcs

► CCT



► Function



► Electrical Parameters



► Photometric Parameters



Finish _____



Marco Linear

Finish



White



Gray




Black



SAA **CE** **RoHS** **UK** **CA**

Marco Linear

LL500



Marco linear is a linkable designed LED lighting. It has the different lighting options, Installation options and different connecting options. and the maximum link length has no limited.

The above various of functions make the marco linear very modern and popular on the office lighting, commercial lighting, retail lighting etc.

► Features

- > Own patent design
- > Multiple link without limited
- > Various of lighting / Installation / connection options
- > CCT and wattage adjustable
- > DALI / Bluetooth / WIFI control
- > 5 years warranty

► Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
LL500-04W-KNT1-36F01-00	36W	typ.4350	typ.125	Y	L1200 X W55 X H80	12.5kg	5pcs
LL501-04W-KNT1-36F01-00	36W	typ.4350	typ.125	Y	L1200 X W55 X H80	12.5kg	5pcs

► CCT



► Function



► Electrical Parameters




► Photometric Parameters




Lighting Options



Installation Method





Case Options




Illuminated connectors

in the shapes X, L and T for the design of formations according to individual wishes




Design Profile



Polo Suspend Linear

Polo Suspend Linear LL400



Polo suspend linear is a UP/down linear lighting which has various of function on the junction box on the ceiling Direct/indirect lighting combination, CCT adjustable, emergency and sensor function. Application for resident, commercial, office, educational, architectural, decorative.



Features

- > Separate control of the direct and indirect light.
- > 120cm 36W Down+6W Up, 150cm 50W Down+6W Up
- > Constructed by Aluminum for heating dispatching
- > 3 steps switch for Tri-color option
- > The driver, EM kits, Sensor is built-in the junction box
- > Easy Installation

► CCT



► Function



► Electrical Parameters



► Photometric Parameters



► Finish



► Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
LL400-04W-SN1-36F01-00	36W	typ.3780	typ.105	Y	L1122 X W40 X H100	15.7kg	5pcs
LL400-04W-SN1-50F01-00	50W	typ.5250	typ.105	Y	L1122 X W40 X H100	15.7kg	5pcs
LL400-05W-SN1-50F01-00	50W	typ.5250	typ.105	Y	L1422 X W40 X H100	19.7kg	5pcs

Design Profile



Push Fit Terminals
Providing hassle free and quick installations

LiFePO4 -IRON BATTERIES
-3 hours Emergency Operation

Emergency Indicator
A visible indicator to highlight the lights battery back up status.


End Cap

LED Strip

Emergency Converter
Ensures there is lighting in case of emergency

Piano Key Terminals
For easy wiring and quick installation


Gear Tray





T8 Slim Batten

BT200




The T8 slim batten have super simple construction and superior capability, with milky, PC diffuser achieves anti-glare and high light transmittance. It is high efficient product with quite large potential market. Integrated 3CCTs to provide flexibility to customer. 4 standard sizes are replacement for T8/T5 fluorescent fitting perfectly.

► Features

- > Patent design for T8 fluorescent fitting
- > End or rear cable entry
- > Multiple Link through end rear
- > Easy installation
- > 5 years warranty



► CCT



► Function



► Electrical Parameters



► Photometric Parameters



► Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
BT200-02W-DN1-10F01-00	10W	typ.1600	typ.160	Y	L600 X W55 X H58	6.4kg	10pcs
BT200-04W-DN1-17F01-00	17W	typ.2720	typ.160	Y	L1200 X W55 X H58	11.3kg	10pcs
BT200-04W-DN1-32F01-00	32W	typ.5120	typ.160	Y	L1200 X W55 X H58	11.3kg	10pcs
BT200-05W-DN1-28F01-00	28W	typ.4480	typ.160	Y	L1500 X W55 X H58	14.5kg	10pcs
BT200-05W-DN1-56F01-00	56W	typ.8960	typ.160	Y	L1500 X W55 X H58	14.5kg	10pcs
BT200-06W-DN1-32F01-00	32W	typ.5120	typ.160	Y	L1800 X W55 X H58	17.8kg	10pcs
BT200-06W-DN1-62F01-00	62W	typ.9920	typ.160	Y	L1800 X W55 X H58	17.8kg	10pcs




Finish _____





Narrow Slim Batten

BT202




Narrow slim batten is offers a homogeneous light output and has a slim housing. 80 degree beam angle focus on the light area, widely used warehouse, corridor, office, factories, supermarkets, etc. It offers ultra-high efficiency up to 160lm/w utilising latest LED chip technology.

Features

- > Own design for traditional fluorescent batten
- > End or rear cable entry
- > Multiple Link through end hole
- > Easy installation
- > 5 years warranty

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
BT202-04W-DN1-17F01-00	17W	typ.2720	typ.160	Y	L1200 X W55 X H50	11.3kg	10pcs
BT202-04W-DN1-32F01-00	32W	typ.5120	typ.160	Y	L1200 X W55 X H50	11.3kg	10pcs
BT202-05W-DN1-28F01-00	28W	typ.4480	typ.160	Y	L1500 X W55 X H50	14.5kg	10pcs
BT202-05W-DN1-56F01-00	56W	typ.8960	typ.160	Y	L1500 X W55 X H50	14.5kg	10pcs
BT202-06W-DN1-32F01-00	32W	typ.5120	typ.160	Y	L1800 X W55 X H50	17.8kg	10pcs
BT202-06W-DN1-62F01-00	62W	typ.9920	typ.160	Y	L1800 X W55 X H50	17.8kg	10pcs
BT202-06W-DN1-72F01-00	72W	typ.11520	typ.160	Y	L1800 X W55 X H50	17.8kg	10pcs



Electrical Parameters




Photometric Parameters



Frosted Slim Batten

BT203




Frosted slim batten is a prefect replacement for traditional light. Aluminum housing provides an excellent thermal management. Opal PC diffuser provide high transparency. Excellent appearance is suitable for various high-end offices, hotel lobbies, conference rooms, classrooms.

Features

- > Own design for traditional fluorescent batten
- > End or rear cable entry
- > Multiple Link through end hole
- > Easy installation
- > 5 years warranty

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
BT203-02W-DN1-10F01-00	10W	typ.1600	typ.160	Y	L600 X W55 X H64	5.8kg	8pcs
BT203-04W-DN1-17F01-00	17W	typ.2720	typ.160	Y	L1200 X W55 X H64	11.5kg	8pcs
BT203-04W-DN1-32F01-00	32W	typ.5120	typ.160	Y	L1200 X W55 X H64	11.5kg	8pcs
BT203-05W-DN1-28F01-00	28W	typ.4480	typ.160	Y	L1500 X W55 X H64	14.5kg	8pcs
BT203-05W-DN1-56F01-00	56W	typ.8960	typ.160	Y	L1500 X W55 X H64	14.5kg	8pcs
BT203-06W-DN1-32F01-00	32W	typ.5120	typ.160	Y	L1800 X W55 X H64	17.0kg	8pcs
BT203-06W-DN1-62F01-00	62W	typ.9920	typ.160	Y	L1800 X W55 X H64	17.0kg	8pcs




Electrical Parameters




Photometric Parameters





Upton Frosted

BT210 | 80mm



Frosted batten is a prefect replacement for traditional light. Aluminum housing provides an excellent thermal management. Opal PS diffuser provide high transparency. Excellent appearance is suitable for various high-end offices, hotel lobbies, conference rooms, classrooms.

Features

- > Own design for traditional fluorescent batten
- > End or rear cable entry
- > Multiple Link through end hole
- > Easy installation
- > 5 years warranty

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
BT210-02W-KN1-10F01-00	10W	typ.1200	typ.120	Y	L600 X W80 X H64	7.0kg	6pcs
BT210-04W-KN1-17F01-00	17W	typ.2040	typ.120	Y	L1200 X W80 XH64	12.0kg	6pcs
BT210-04W-KN1-34F01-00	34W	typ.4080	typ.120	Y	L1200 X W80 X H64	12.0kg	6pcs
BT210-05W-KN1-22F01-00	22W	typ.2640	typ.120	Y	L1500 X W80 X H64	14.0kg	6pcs
BT210-05W-KN1-40F01-00	40W	typ.4800	typ.120	Y	L1500 X W80 X H64	14.0kg	6pcs
BT210-06W-KN1-27F01-00	27W	typ.3240	typ.120	Y	L1800 X W80 X H64	18.0kg	6pcs
BT210-06W-KN1-50F01-00	50W	typ.6000	typ.120	Y	L1800 X W80 X H64	18.0kg	6pcs



Electrical Parameters




Photometric Parameters



Kingston Frosted

BT220 | 120mm



Frosted batten is a prefect replacement for traditional light. Aluminum housing provides an excellent thermal management. Opal PS diffuser provide high transparency. Excellent appearance is suitable for various high-end offices, hotel lobbies, conference rooms, classrooms.

Features

- > Own design for traditional fluorescent batten
- > End or rear cable entry
- > Multiple Link through end hole
- > Easy installation
- > 5 years warranty

Data Sheet


Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
BT220-02W-KN1-10F01-00	10W	typ.1200	typ.120	Y	L600 X W120 X H64	7.0kg	4pcs
BT220-04W-KN1-17F01-00	17W	typ.2040	typ.120	Y	L1200 X W120 X H64	10.5kg	4pcs
BT220-04W-KN1-34F01-00	34W	typ.4080	typ.120	Y	L1200 X W120 X H64	10.5kg	4pcs
BT220-04W-KN1-22F01-00	22W	typ.2640	typ.120	Y	L1500 X W120 X H64	13.0kg	4pcs
BT220-05W-KN1-40F01-00	40W	typ.4800	typ.120	Y	L1500 X W120 X H64	13.0kg	4pcs
BT220-06W-KN1-27F01-00	27W	typ.3240	typ.120	Y	L1800 X W120 X H64	15.5kg	4pcs
BT220-06W-KN1-50F01-00	50W	typ.6000	typ.120	Y	L1800 X W120 X H64	15.5kg	4pcs



Electrical Parameters




Photometric Parameters





Hilton Frosted

BT230 | 150mm




Frosted batten is a prefect replacement for traditional light. Aluminum housing provides an excellent thermal management. Opal PS diffuser provide high transparency. Excellent appearance is suitable for various high-end offices, hotel lobbies, conference rooms, classrooms.

Features

- > Own design for traditional fluorescent batten
- > End or rear cable entry
- > Multiple Link through end hole
- > Easy installation
- > 5 years warranty

Data Sheet


Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
BT230-02W-KN1-10F01-00	10W	typ.1200	typ.120	Y	L600 X W150 X H64	7.0kg	6pcs
BT230-04W-KN1-17F01-00	17W	typ.2040	typ.120	Y	L1200 XW150 X H64	12.0kg	6pcs
BT230-04W-KN1-34F01-00	34W	typ.4080	typ.120	Y	L1200 X W150 X H64	12.0kg	6pcs
BT230-05W-KN1-22F01-00	22W	typ.2640	typ.120	Y	L1500 X W150 X H64	14.0kg	6pcs
BT230-05W-KN1-40F01-00	40W	typ.4800	typ.120	Y	L1500 X W150 X H64	14.0kg	6pcs
BT230-06W-KN1-27F01-00	27W	typ.3240	typ.120	Y	L1800 X W150 X H64	18.0kg	6pcs
BT230-06W-KN1-50F01-00	50W	typ.6000	typ.120	Y	L1800 X W150 X H64	18.0kg	6pcs



Electrical Parameters




Photometric Parameters



Kaston Frosted

BT240 | 200mm



Frosted batten is a prefect replacement for traditional light. Aluminum housing provides an excellent thermal management. Opal PS diffuser provide high transparency. Excellent appearance is suitable for various high-end offices, hotel lobbies, conference rooms, classrooms.

Features

- > Own design for traditional fluorescent batten
- > End or rear cable entry
- > Multiple Link through end hole
- > Easy installation
- > 5 years warranty

Data Sheet


Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
BT240-02W-KN1-10F01-00	10W	typ.1200	typ.120	Y	L600 X W200 X H64	7.0kg	4pcs
BT240-04W-KN1-17F01-00	17W	typ.2040	typ.120	Y	L1200 X W200 X H64	10.5kg	4pcs
BT240-04W-KN1-34F01-00	34W	typ.4080	typ.120	Y	L1200 X W200 X H64	10.5kg	4pcs
BT240-04W-KN1-22F01-00	22W	typ.2640	typ.120	Y	L1500 X W200 X H64	13.0kg	4pcs
BT240-05W-KN1-40F01-00	40W	typ.4800	typ.120	Y	L1500 X W200 X H64	13.0kg	4pcs
BT240-06W-KN1-27F01-00	27W	typ.3240	typ.120	Y	L1800 X W200 X H64	15.5kg	4pcs
BT240-06W-KN1-50F01-00	50W	typ.6000	typ.120	Y	L1800 X W200 X H64	15.5kg	4pcs



Electrical Parameters




Photometric Parameters





Wega Batten


BT330



Safety-lock-mechanism design for quick installation. Osram driver as standard and adopts SMD high lumen efficiency 160LM/W is good lighting solution. The iron lamp body provides excellent heat dissipation.

Features

- > High lumen efficiency – up to 160lm/w
- > Safety-lock-mechanism for a secure installation
- > Durable sheet-metal casing with end/rear cables entries
- > Milky PC cover with 85% transparency and 120° beam angle
- > Suitable for surface mounting or suspended installation
- > Perfect replacement for traditional T5/T8 fittings
- > OSRAM driver as standard
- > 5 year warranty



Electrical Parameters




Photometric Parameters



General Batten

BT310



General Batten adopts separated module design, has been improved to have a wider lighting emitting area. Color temperature and wattage both switchable. Mounting design: suspension/surface mounting

Features

- > Various of functions for options
- > High lumen output at 160LM/W
- > Easy Installation
- > 5 years warranty



Electrical Parameters



Photometric Parameters



Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
BT330-02W-DN1-10F01-00	10W	typ.1600	typ.160	Y	L600 X W55 X H59	7.5kg	10pcs
BT330-04W-DN1-18F01-00	18W	typ.2880	typ.160	Y	L1200 X W55 X H59	12.4kg	10pcs
BT330-04W-DN1-35F01-00	35W	typ.5600	typ.160	Y	L1200 X W55 X H59	12.4kg	10pcs
BT330-05W-DN1-29F01-00	29W	typ.4640	typ.160	Y	L1500 X W55 X H59	14.5kg	10pcs
BT330-05W-DN1-55F01-00	55W	typ.8800	typ.160	Y	L1500 X W55 X H59	15.5kg	10pcs
BT330-06W-DN1-35F01-00	35W	typ.5600	typ.160	Y	L1800 X W55 X H59	18.8kg	10pcs
BT330-06W-DN1-55F01-00	55W	typ.8800	typ.160	Y	L1800 X W55 X H59	18.8kg	10pcs


Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
BT310-04W-DT1-17F01-00	17W	typ.2720	typ.160	Y	L1200 X W152 X H77	9.2kg	4pcs
BT310-04W-DT1-32F01-00	32W	typ.5120	typ.160	Y	L1200 X W152 X H77	9.2kg	4pcs
BT310-05W-DT1-25F01-00	25W	typ.4000	typ.160	Y	L1500 X W152 X H77	11.2kg	4pcs
BT310-05W-DT1-50F01-00	50W	typ.8000	typ.160	Y	L1500 X W152 X H77	11.2kg	4pcs



TX Batten

BT320



TX Batten adopts unique module design to have a wide lighting emitting area, the semi-circular shape makes it emit a uniform light effect, bringing a high-level texture. Color temperature and wattage both switchable. Suspension/surface mounting designed for school lighting, office lighting applications, etc.

Features

- > Various of functions for options
- > High lumen output at 160LM/W
- > Easy Installation
- > 5 years warranty


Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
BT320-04W-DN1-20F01-00	20W	typ.3200	typ.160	Y	L1190 X W165 X H75	11.8kg	5pcs
BT320-04W-DN1-34 F01-00	34W	typ.5440	typ.160	Y	L1190 X W165 X H75	11.8kg	5pcs
BT320-05W-DN1-24F01-00	24W	typ.3840	typ.160	Y	L1470 X W165 X H75	14.0kg	5pcs
BT320-05W-DN1-40F01-00	40W	typ.6400	typ.160	Y	L1470 X W165 X H75	14.0kg	5pcs
BT320-06W-DN1-32F01-00	32W	typ.5120	typ.160	Y	L1800 X W165 X H75	17.7kg	5pcs
BT320-06W-DN1-50F01-00	50W	typ.8000	typ.160	Y	L1800 X W165 X H75	17.7kg	5pcs



Grid Batten

BT340



Grid batten use the special designed steel grid to make the UGR data. It is the best LED module to replace the similar traditional light.

Features

- > Various of functions for options
- > High lumen output at 160LM/W
- > Easy Installation
- > 5 years warranty

Data Sheet


Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
BT340-04W-PN1-35F01-00	21-35W	2150-4900	typ.140	Y	L1200 X W200 X H55	23.5kg	5pcs
BT340-04W-PN1-40F01-00	23-40W	3650-5600	typ.140	Y	L1500 X W200 X H55	23.5kg	5pcs



Electrical Parameters




Photometric Parameters



Electrical Parameters



Photometric Parameters



Arco Batten

BT300



Arco batten is a extra wide body LED batten featuring an aesthetically pleasing low-glare design , The arco batten has a multiple function ,All of these special design make the arco batten is a best replacement for the traditional fluorescent college fitting

The arco batten were widely use in offices, universities colleges, schools, hospitals.

Features

- > College Fitting / College Batten
- > 0.7mm steel case +1.8mm TP(b) cover
- > Safety lock to prevent accidental opening
- > Various of functions for options
- > High lumen output at 160LM/W
- > Rotatable end cap for easy opening and installation
- > 5 years warranty

Polycarbonate
Diffuser End Cap

Frosted Polycarbonate Diffuser

CCT Switch

With DIP switch

Wiring Terminals

LED PCB

Base End Cap


With conduit knockouts holes(20mm)

Steel Base with BESA

► Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
BT300-04W-DT1-17F01-00	17W	typ.1600	typ.160	Y	L1200 X W215 X H77	17.5kg	5pcs
BT300-04W-DT1-32F01-00	32W	typ.5120	typ.160	Y	L1200 X W215 X H77	17.5kg	5pcs
BT300-05W-DT1-25F01-00	25W	typ.4000	typ.160	Y	L1500 X W215 X H77	21.6kg	5pcs
BT300-05W-DT1-50F01-00	50W	typ.8000	typ.160	Y	L1500 X W215 X H77	21.6kg	5pcs
BT300-05W-DT1-60F01-00	60W	typ.9600	typ.160	Y	L1500 X W215 X H77	21.6kg	5pcs

► CCT



► Electrical Parameters



► Function




► Photometric Parameters





Recessed UGR Batten

LL602




Recessed Batten provides clean lines of light with a simple easy-to-use design. It sits flush to the surface and is ideal for under-cabinet lighting, toe kick lighting, area lighting, wall and ceiling inset lighting.

► Features

- > Surface linear suitable for educational and commercial applications
- > Aluminium body with polycarbonate diffuser and plastic end caps
- > Installation clips easy for Plaster Ceiling installation



► CCT



► Function



► Electrical Parameters




► Photometric Parameters




► Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
TP-LL602-04W-KT1-36F01-01	36W	typ.3960	typ.110	Y	L1209 X W68 X H30.5	9.3kg	10pcs
TP-LL602-05W-KT1-48F01-01	48W	typ.5200	typ.110	Y	L1509 X W68 X H30.5	11.6kg	10pcs



Recessed Frosted Batten

LL601




Recessed Batten provides clean lines of light with a simple easy-to-use design. It sits flush to the surface and is ideal for under-cabinet lighting, toe kick lighting, area lighting, wall and ceiling inset lighting.

► Features

- > Surface linear suitable for educational and commercial applications
- > Aluminium body with polycarbonate diffuser and plastic end caps
- > Installation clips easy for Plaster Ceiling installation



► CCT



► Function



► Electrical Parameters



► Photometric Parameters



► Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
TP-LL601-04W-KT1-36F01-01	36W	typ.3960	typ.110	Y	L1209 X W68 X H30.5	9.3kg	10pcs
TP-LL601-05W-KT1-48F01-01	48W	typ.5200	typ.110	Y	L1509 X W68 X H30.5	11.6kg	10pcs



Retro Flex


LL200 | Honeycomb LL201

| PC Cover

LL202 | Lens 90 degree

LL203 | Lens L/R 25

degree



Retro flex lighting module include pre-wired PC cover (160LM/W) module and honeycomb(125LM/W) module , CLO function makes 7 years warranty ,25-75W adjustable makes stock easy to handle,Tri color suitable for different applications.

Features


- > Up to 160LM/W@12000LM
- > UGR<19 (honeycomb cover)
- > 400V Switcher for 3-phase AC
- > 5/7 pre-wired system with CLO function
- > Click-Slide system allows the module to be mounted on variety of trunks
- > Tool free installation at MAX 200M multiple link
- > 7 years warranty

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
LL200-05W-DT1-75F01-00	25-75W	typ.3500-10500	typ.140	Y	L1526 X W106 X H88	21.5kg	8pcs
LL201-05W-CT1-75F01-00	25-75W	typ.4000-12000	typ.160	Y	L1526 X W106 X H88	16.5kg	8pcs
LL202-05W-CT1-75F01-00	25-75W	typ.4000-12000	typ.160	Y	L1526 X W106 X H88	16.5kg	8pcs
LL203-05W-CT1-75F01-00	25-75W	typ.4000-12000	typ.160	Y	L1526 X W106 X H88	16.5kg	8pcs



CCT



Function



Electrical Parameters



Photometric Parameters



Wiring



Finish




Traditional trunk complete with

Beam Angle : 30/60/90/LR25 Degree

Compatible with various brands traditional trunks

Width: Max 68mm, Min 42mm



Connection Method



Trunk rail and Blank cover (IINNO Standard)

For the applications have no the traditional trunk or the new buildings . IINNO can provide the standard trunk for the retro flex lighting module . And also, We provide the blank cover for the additional balance length for the installation

Trunk Rail

Product Picture	Order Code	Product Name	Dimension (mm)	Dimension drawing
	RM-TR05-00	5ft-150CMM/ Trunk Rail	L1527 X W64.5 X H50	
	RM-TR10 -00	10ft-300CM/ Trunk Rail	L3027 X W64.5 X H50	

Blank cover

Product Picture	Order Code	Product Name	Dimension (mm)	Dimension drawing
	RM-BC01-00	1ft-30CMM/Blank Cover	L327 X W64.5 X H37	
	RM-BC04-00	4ft-120CM/Blank Cover	L1227 X W64.5 X H37	
	RM-BC05-00	5ft-150CMM/Blank Cover	L1527 X W64.5 X H37	

Design Profile



Each universal module enable tool-free 7-level power regulation via DIP switch:
25W-35W-40W-45W-55W-65W-75W

The newly developed LED driver regulates the luminous flux intelligently and automatically. In this way is constant over the entire service life Light level guaranteed and economical operation secured.

The unique soft start technology reduces high inrush currents and saves money. it protects electrical components and thus extends the operating time and service life

WW NW CW

CCT Switch enables the selection the desired color temperature (3000 K - 4000 K - 5000 K) simply select using the DIP switch.

▲L1 ▲L2 ▲L3

The 400V /3-phase AC switcher makes the Retro Flex Module can be max 200 meters multiple linking

Tool-free phase selection, this saves you a rewiring and thus valuable time.



Safety rope hanging board


① ② ③ ④ ⑤ ⑥

Smart click-slide installation clips for renovation or conversion of all common T5 and T8 light line systems


Easy assembly/disassembly Flexible arrangement in the mounting rail, enables a 1-person conversion.

Male and female connector quick connect, tool free, save valuable time during of assembly


Installation/connection method




Quick Connect Clip



Fast Connector



Installation




Suspension

Magnet tool free installation

Surface Mounting



Pro-Line



Pro-Line is a complete LED solutions designed for shelf led lighting by Magnet tool free installation. And it's also widely used in the office /commercial / industrial / education applications.
The batterns can be connected through the end by quick Wieland connector. This allows end to end continous tool free installation.

- Features
 - > Up to 160lm/W
 - > Quick Wieland Connector For Multiple Link
 - > Magnet tool-free Installation / Surface Mounted / Suspension
 - > 5 years warranty



► CCT

Single Color

3000K4000K5000K6000K

Tri-color

3000K4000K5000K6000K

► Function

ON OFFPR

► Electrical Parameters

AC200-240VPF≥0.95THD<15%Flicker Free

► Photometric Parameters

120LM/W140LM/W160LM/WCRI>80SDCM<5LM79TM-21ERP2.0

► Wiring

Double wiring

► Finish

WhiteGrayBlack

► T8 Module (120°)

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
LL307-02W-CN1-10F01-00	10W	typ.1600	typ.160	Y	L600 X W55 X H58	6.4kg	10pcs
LL307-04W-CN1-17F01-00	17W	typ.2720	typ.160	Y	L1200 X W55 X H58	11.3kg	10pcs
LL307-04W-CN1-32F01-00	32W	typ.5120	typ.160	Y	L1200 X W55 X H58	11.3kg	10pcs
LL307-05W-CN1-28F01-00	28W	typ.4480	typ.160	Y	L1500 X W55 X H58	14.5kg	10pcs
LL307-05W-CN1-56F01-00	56W	typ.8960	typ.160	Y	L1500 X W55 X H58	14.5kg	10pcs
LL307-06W-CN1-32F01-00	32W	typ.5120	typ.160	Y	L1800 X W55 X H58	17.8kg	10pcs
LL307-06W-CN1-62F01-00	62W	typ.9920	typ.160	Y	L1800 X W55 X H58	17.8kg	10pcs

► Lens Module (30°/60°/90°/LR25 Optional)

Order Code	Wattage	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
LL300-02W-CN1-10F01-00	10W	typ.1600	typ.160	Y	L600 X W55 X H63.5	6.8kg	8pcs
LL300-04W-CN1-17F01-00	17W	typ.2720	typ.160	Y	L1200 X W55 X H63.5	12.5kg	8pcs
LL300-04W-CN1-32F01-00	32W	typ.5120	typ.160	Y	L1200 X W55 X H63.5	12.5kg	8pcs
LL300-05W-CN1-28F01-00	28W	typ.4480	typ.160	Y	L1500 X W55 X H63.5	15.5kg	8pcs
LL300-05W-CN1-56F01-00	56W	typ.8960	typ.160	Y	L1500 X W55 X H63.5	15.5kg	8pcs
LL300-06W-CN1-32F01-00	32W	typ.5120	typ.160	Y	L1800 X W55 X H63.5	18.0kg	8pcs
LL300-06W-CN1-62F01-00	62W	typ.9920	typ.160	Y	L1800 X W55 X H63.5	18.0kg	8pcs

► Frosted Module

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
LL304-02W-CN1-10F01-00	10W	typ.1600	typ.160	Y	L600 X W55 X H63.5	5.8kg	8pcs
LL304-04W-CN1-17F01-00	17W	typ.2720	typ.160	Y	L1200 X W55 X H63.5	11.5kg	8pcs
LL304-04W-CN1-32F01-00	32W	typ.5120	typ.160	Y	L1200 X W55 X H63.5	11.5kg	8pcs
LL304-05W-CN1-28F01-00	28W	typ.4480	typ.160	Y	L1500 X W55 X H63.5	14.5kg	8pcs
LL304-05W-CN1-56F01-00	56W	typ.8960	typ.160	Y	L1500 X W55 X H63.5	14.5kg	8pcs
LL304-06W-CN1-32F01-00	32W	typ.5120	typ.160	Y	L1800 X W55 X H63.5	17.0kg	8pcs
LL304-06W-CN1-62F01-00	62W	typ.9920	typ.160	Y	L1800 X W55 X H63.5	17.0kg	8pcs

► Gentle Module (Low glare UGR<22)

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
LL305-02W-KN1-10F01-00	10W	typ.1200	typ.120	Y	L605 X W55 X H63.5	6.0kg	8pcs
LL305-04W-KN1-17F01-00	17W	typ.2040	typ.120	Y	L1205 X W55 X H63.5	11.5kg	8pcs
LL305-04W-KN1-34F01-00	34W	typ.4080	typ.120	Y	L1205 X W55 X H63.5	11.5kg	8pcs
LL305-05W-KN1-22F01-00	22W	typ.2640	typ.120	Y	L1505 X W55 X H63.5	14.5kg	8pcs
LL305-05W-KN1-40F01-00	40W	typ.4800	typ.120	Y	L1505 X W55 X H63.5	14.5kg	8pcs
LL305-06W-KN1-27F01-00	27W	typ.3240	typ.120	Y	L1805 X W55 X H63.5	17.0kg	8pcs
LL305-06W-KN1-50F01-00	50W	typ.6000	typ.120	Y	L1805 X W55 X H63.5	17.0kg	8pcs

► Narrow Module (80°)

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
LL306-02W-CN1-10F01-00	10W	typ.1600	typ.160	Y	L605 X W55 X H50	5.7kg	10pcs
LL306-04W-CN1-17F01-00	17W	typ.2720	typ.160	Y	L1200 X W55 X H50	11.3kg	10pcs
LL306-04W-CN1-32F01-00	32W	typ.5120	typ.160	Y	L1200 X W55 X H50	11.3kg	10pcs
LL306-05W-CN1-28F01-00	28W	typ.4480	typ.160	Y	L1500 X W55 X H50	14.5kg	10pcs
LL306-05W-CN1-56F01-00	56W	typ.8960	typ.160	Y	L1500 X W55 X H50	14.5kg	10pcs
LL306-06W-CN1-32F01-00	32W	typ.5120	typ.160	Y	L1800 X W55 X H50	17.8kg	10pcs
LL306-06W-CN1-62F01-00	62W	typ.9920	typ.160	Y	L1800 X W55 X H50	17.8kg	10pcs
LL306-06W-CN1-72F01-00	72W	typ.11520	typ.160	Y	L1800 X W55 X H50	17.8kg	10pcs

► Accessory


Order Code	Product name
ASS-WIR-F318FU-1500-00	1500mm EU Plug Connector
ASS-WIR-F318FU-2000-04	2000mm EU Plug Connector
ASS-WIR-F318FU-3000-00	3000mm EU Plug Connector
ASS-WIR-F318FU-0300-01	300mm Male & Female Connector
ASS-WIR-F318FU-0900-01	900mm Male & Female Connector
ASS-WIR-F318FU-1500-01	1500mm Male & Female Connector
ASS-WIR-F315FU-2000-00	2000mm Male & Female Connector





Fasco Asymmetric


AL100



The fasco asymmetric light is a recessed Led light with the milkey diffuser, The aluminum heat sink helps the fasco asymmetric light offer a long life time by 5 years warranty.

Features

- > Aluminum heat sink
- > Special asymmetric design with milky cover
- > Recessed installation
- > 5 years warranty



Electrical Parameters



Photometric Parameters




Data Sheet

Order Code	Rated Power	Lumen	LM/W	Cut-out Size (mm)	Dimension (mm)	GW/CTN	QTY/CTN
AL100-04W-PT1-28F01-00	18-28W	typ.2160-3360	typ.120	1175 X 120	L1195 X W140 X H80	13.5kg	4pcs



Dasco Asymmetric

AL200



The dasco asymmetric light is a surface mounting Led light with the milky diffuser, The aluminum heat sink helps the dasco asymmetric light offer a long life time by 5 years warranty.

Features

- > Aluminum heat sink
- > Special asymmetric design with milky cover
- > Surface mounting installation
- > 5 years warranty



Electrical Parameters



Photometric Parameters




Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
AL100-04W-DT1-25F01-00	15-25W	typ.2100-3500	typ.140	Y	L1200 X W102.5 X H102.5	13.5kg	4pcs



Track Asymmetric

AL300



The track asymmetric light is sepcial design which with the track installation, it was widely used on the retail application because it has 2 side lightng emmitting . Aluminum case is an excellent heating sink, the high technology SMD2835 provide a more higher lumen output.

► Features

- > Aluminum heat sink
- > Special 2 side lighting
- > Track installation
- > 5 years warranty

► Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
AL300-04W-CN1-38D01-00	Down 32W+Up 6W	typ.6000	typ.160	Y	L1200 X W86 X H97.5	14kg	4pcs
AL300-05W-CN1-47D01-00	Down 40W+Up 7W	typ.7500	typ.160	Y	L1500 X W86 X H97.5	17kg	4pcs



► CCT

Single Color

3000K
4000K
5000K
6000K

Tri-color

2700K
3000K
3500K
4000K
4500K
5000K
5500K
6000K

► Function

ON OFF

1-10V Dimming

DALI

MS

PIR

Emergency

► Electrical Parameters

AC 200-240V

PF ≥0.95

THD <15%

Flicker Free

► Photometric Parameters

160 LM/W

CRI>80
SDCM <3

LM79 TM-21

ERP2.0

Tri-proof Lights

- >The aluminum tri-proof lights are a new modern design which with more function options and up to 160LM/W.
- >All of aluminum tri-proof lights are IP65 and IK10 protected,the different options make the clients use the aluminum tri-proof lights on differents applications, Such as: Car parks, Factories, ect.



Categories



Prime Tri-proof
TR100



Deco Tri-proof
TR200



Deco S Tri-proof
TR200



Basic Tri-proof
TR300



Tubar Light
TR400



NCF Luminaires
TR500



NCF Luminaires
TR600




Design Profile



IP65
IK10
UP to 160LM/W

Prime Tri-proof TR100



Prime tri-proof is a tool free multi connected fitting which with various of function options as be showed on this catalogue.

The excellent heating sink, function options and multi connecting make it has a wide range of used in different applications.

Features


- > Quick snap end caps for easy installation
- > CCT & Wattage adjustable on end cap.
- > 5 wires 3 phase for more quantity linkable
- > 160LM/W high lumen efficacy
- > Single or linkable installation
- > 5 years warranty

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
TR100-02W-DN1-22F01-00	22W	typ.3500	typ.160	Y	L625 X W85 X H73	6.5kg	4pcs
TR100-04W-DN1-40F01-00	40W	typ.6400	typ.160	Y	L1200 X W85 X H73	9.5kg	4pcs
TR100-04W-DN1-60F01-00	60W	typ.9600	typ.160	Y	L1200 X W85 X H73	9.5kg	4pcs
TR100-05W-DN1-40F01-00	40W	typ.6400	typ.160	Y	L1500 X W85 X H73	12.5kg	4pcs
TR100-05W-DN1-60F01-00	60W	typ.9600	typ.160	Y	L1500 X W85 X H73	12.5kg	4pcs
TR100-08W-DN1-1BF01-00	100W	typ.16000	typ.160	Y	L2400 X W85 X H73	19.0kg	4pcs



CCT	Single Color 3000K 4000K 5000K 6000K	Tri-color	
Function	 ON OFF	 1-10V Dimming	
	 MS	 Daylight Sensor	 PIR
			 Emergency
Electrical Parameters	 AC 200-240V		 PF ≥0.95
			 THD <15%
			 Flicker Free
Photometric Parameters	 120 LM/W	 140 LM/W	 160 LM/W
	 CRI>80 SDCM <5	 LM79 TM-21	 ERP2.0
Wiring	 Single wiring	 Double wiring	 3wires 3Phase
			 5wires 3Phase
			 7wires 3Phase
IP/IK	 IP65	 IK10	



Function options

- > CCT switch
- > Wattage switch
- > EM testing switch
- > MS switch
- > 3 phase switch
- > 3/5/7 wires terminal



Design Profile

Dimmable Driver

Polycarbonate cover

LED PCB

Terminal for Quick Installation

Waterproof plug IP65

Aluminum Profile for heat dissipation

Grey Tray for easy replacement

Deco Tri-proof

TR200



Deco tri-proof is new design which use the gear tray to realize the function options. The gear tray is taken put from the end cap.


The excellent heating sink, function options and multi connecting make it has a wide range of used in different applications.

Features

- > Quick snap end caps for easy installation
- > Easy for LED driver replacement
- > CCT & Wattage adjustable
- > 160LM/W with high lumen efficacy
- > Single or linkable installation
- > 5 years warranty



CCT



Function



Electrical Parameters



Photometric Parameters



Wiring



IP/IK




Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
TR200-02W-DN1-22F01-00	22W	typ.3500	typ.160	Y	L625 X W85 X H73	6.5kg	4pcs
TR200-04W-DN1-40F01-00	40W	typ.6400	typ.160	Y	L1200 X W85 X H73	9.5kg	4pcs
TR200-04W-DN1-60F01-00	60W	typ.9600	typ.160	Y	L1200 X W85 X H73	9.5kg	4pcs
TR200-05W-DN1-40F01-00	40W	typ.6400	typ.160	Y	L1500 X W85 X H73	12.5kg	4pcs
TR200-05W-DN1-60F01-00	60W	typ.9600	typ.160	Y	L1500 X W85 X H73	12.5kg	4pcs
TR200-08W-DN1-1BF01-00	100W	typ.16000	typ.160	Y	L2400 X W85 X H73	19.0kg	4pcs

Deco S Tri-proof

TR600



Deco S tri proof light with high lumen, waterpoo IP65 and IK08, 140lm/w, a reliable and professional lighting solution. Perfect Balance between cost & performance !

Features

- > Special design for back wiring
- > IP65 and IK08 for all industrial areas of application
- > Durable insulated power driver
- > Newest technology of SMD2835 LED
- > No UV or IR and completely mercury free
- > L80/B10 @ 50.000h
- > 5 years warranty

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
TP-TR600-02N-DT1-15F01-01	15W	typ.2250	typ.150	Y	L600 X W65 X H55	7.8kg	4pcs
TP-TR600-04N-DT1-34F01-01	20W	typ.3000	typ.150	Y	L1200 X W65 X H55	12.5kg	4pcs
TP-TR600-04N-DT1-20F01-01	34W	typ.5100	typ.150	Y	L1200 X W65 X H55	12.5kg	4pcs
TP-TR600-05N-DT1-28F01-01	28W	typ.4200	typ.150	Y	L1500 X W65 X H55	14.5kg	4pcs
TP-TR600-05N-DT1-56F01-01	56W	typ.8400	typ.150	Y	L1500 X W65 X H55	14.5kg	4pcs
TP-TR600-06N-DT1-32F01-01	32W	typ.4800	typ.150	Y	L1800 X W65 X H55	24.0kg	4pcs
TP-TR600-06N-DT1-65F01-01	65W	typ.9750	typ.150	Y	L1800 X W65 X H55	14.5kg	4pcs

CCT	Single Color	3000K	4000K	5000K	6000K
Function	ON-OFF	1-10V Dimming	DALI	PIR	
Electrical Parameters	AC 200-240V		PF ≥0.95	THD <15%	Flicker Free
Photometric Parameters	130 LM/W	150 LM/W	CRI>80 SDCM <5	LM79 TM-21	ERP2.0
Wiring	Single wiring	Double wiring	3wires 3Phase	5wires 3Phase	
IP/IK	IP65	IK08			


Design Profile





Basic Tri-proof

TR300



Basic Tri-proof light which were widely used on warehouses, factories, car parks, sports facilities etc. Outdoor, indoor commercial & industrial applications.

The Aluminum casing provides excellent heating dissipation, The high technology SMD2835 provide a more higher lumen output, up to 160lm/W.

Features

- > IP65/IK10 approval
- > Single or multiple link
- > 5 years warranty

Data Sheet


Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
TR300-02W-DN1-22F01-00	22W	typ.3500	typ.160	Y	L625 X W85 X H78	7.8kg	4pcs
TR300-04W-DN1-40F01-00	40W	typ.6400	typ.160	Y	L1225 X W85 X H78	12.5kg	4pcs
TR300-04W-DN1-60F01-00	60W	typ.9600	typ.160	Y	L1225 X W85 X H78	12.5kg	4pcs
TR300-05W-DN1-40F01-00	40W	typ.6400	typ.160	Y	L1525 X W85 X H78	14.5kg	4pcs
TR300-05W-DN1-60F01-00	60W	typ.9600	typ.160	Y	L1525 X W85 X H78	14.5kg	4pcs
TR300-08W-DN1-1BF01-00	100W	typ.16000	typ.160	Y	L2425 X W85 X H78	24.0kg	4pcs

CCT	Single Color 3000K 4000K 5000K 6000K			
Function	ON OFF	1-10V Dimming	DALI	PIR
Electrical Parameters	AC 200-240V	PF ≥0.95	THD <15%	Flicker Free
Photometric Parameters	120 LM/W	140 LM/W	160 LM/W	
	CRI>80 SDCM <5	LM79 TM-21	ERP2.0	
Wiring	Single wiring	Double wiring	3wires 3Phase	5wires 3Phase
IP/IK	IP65	IK10		



Tubar Lights

TR400



IP69K Tubar light an ideal solution for chemical cleaning, car washing, food processing and poultry lighting etc. industrial applications.

PMMA case for NH3-Anti Corrosion Resistance, PC Housing for UV Resistance. The high technology SMD2835 provide a more higher lumen output.

Features

- > IP69K / IK10 Protection
- > Single or multiple link
- > 5 years warranty

Data Sheet


Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
TR400-02W-DN1-22F01-00	22W	typ.3050	typ.140	Y	L600 X D78	7.8kg	4pcs
TR400-04W-DN1-40F01-00	40W	typ.5500	typ.140	Y	L1200 X D78	12.5kg	4pcs
TR400-04W-DN1-60F01-00	60W	typ.8400	typ.140	Y	L1200 X D78	12.5kg	4pcs
TR400-05W-DN1-60F01-00	60W	typ.8400	typ.140	Y	L1500 X D78	14.5kg	4pcs

CCT	Single Color 3000K 4000K 5000K 6000K			
Function	ON OFF	1-10V Dimming	DALI	
Electrical Parameters	AC 200-240V	PF ≥0.95	THD <15%	Flicker Free
Photometric Parameters	120 LM/W	140 LM/W	CRI>80 SDCM <5	LM79 TM-21
				ERP2.0
Wiring	Single wiring	Double wiring		
Material	PC	PMMA		
IP/IK	IP69K	IK10		



Single NCF

TR500



Single NCF fitting is a new design to replace the traditional fluorescent fitting. The different lengths are available .
Waterproof, Dust-proof , Corrosion-Proof, is the basic features of the luminaries. Exclusive Quick-fit design for faster installation.

Features

- > Easy Installation with fast connection design
- > End or rear cable entry
- > IP 65 Rating, High impact IK08
- > Single installation or linkable
- > 5 years warranty

CCT

Single Color
3000K
4000K
5000K
6000K

Tri-color
3000K
4000K
5000K

Function

ON OFF
1-10V Dimming

DALI

MS

Emergency

Electrical Parameters

AC
200-240V

PF
≥0.95

THD
<15%

Flicker
Free

Photometric Parameters

120
LM/W

140
LM/W

CRI>80
SDCM
<5

LM79
TM-21

ERP2.0

Wiring

Single
wiring

Double
wiring

IP/IK

IP65

IK08


Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
TR500-02W-DN1-20F01-00	20W	typ.2800	typ.140	Y	L600 X W80 X H75	6.2kg	6pcs
TR500-04W-DN1-30F01-00	30W	typ.4200	typ.140	Y	L1200 X W80 X H75	11.2kg	6pcs
TR500-05W-DN1-25F01-00	25W	typ.3500	typ.140	Y	L1500 X W80 X H75	14.2kg	6pcs
TR500-05W-DN1-50F01-00	50W	typ.7000	typ.140	Y	L1500 X W80 X H75	14.2kg	6pcs
TR500-06W-DN1-30F01-00	30W	typ.4200	typ.140	Y	L1800 X W80 X H75	17.5kg	6pcs
TR500-06W-DN1-50F01-00	50W	typ.7000	typ.140	Y	L1800 X W80 X H75	17.5kg	6pcs



Twins NCF

TR510




Twins NCF fitting is a new design to replace the traditional fluorescent fitting. The different lengths are available .
Waterproof, Dust-proof , Corrosion-Proof, is the basic features of the luminaires. Exclusive Quick-fit design for faster installation.

Features

- > Easy Installation with fast connection design
- > End or rear cable entry
- > IP 65 Rating, High impact IK08
- > Single installation or linkable
- > 5 years warranty



CCT



Function



Electrical Parameters



Photometric Parameters



Wiring




IP/IK



Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
TR510-02W-DN1-22F01-00	20W	typ.2800	typ.140	Y	L600 X W125 X H88	8.64kg	6pcs
TR510-04W-DN1-40F01-00	40W	typ.5600	typ.140	Y	L1200 X W125 X H88	16.0kg	6pcs
TR510-05W-DN1-50F01-00	50W	typ.7000	typ.140	Y	L1500 X W125 X H88	20.4kg	6pcs
TR510-06W-DN1-50F01-00	50W	typ.7000	typ.140	Y	L1800 X W125 X H88	25.5kg	6pcs
TR510-06W-DN1-75F01-00	75W	typ.10500	typ.140	Y	L1800 X W125 X H88	25.5kg	6pcs




Polycarbonate base

Stainless steel assembly clips



MOD 320 BH100



MOD -D320 bulkheads widely use to replace the traditional 2D fluorescent light, The suitable dimension and various of function options make it very popular on the market.

It can reach 120 LM/W and 150 LM/W to help you get a well energy saving.

Features

- > Up to 150 LM/W@ 2400LM
- > IP65 waterproof
- > UV -Anti
- > Various of function options
- > Various of bezels are available
- > Warranty: 5 years

CCT Single Color 3000K
4000K
5000K
6000K Tri-color 2700K
3000K
4000K
5000K

Function F1: ON OFF F4: ON OFF + Emergency + F2: ON OFF + Emergency F5: ON OFF + Self EM F3: ON OFF + MS F6: ON OFF + Self EM + MS

Electrical Parameters AC 200-240V PF ≥0.95 THD <15% Flicker Free

Photometric Parameters 120 LM/W 150 LM/W CRI>80 SDCM <5 LM79 TM-21 ERP2.0

IP Rating IP65

Finish White Silver Black

Data Sheet


Order Code	Rated Power	Lumen	LM/W	Function	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
BH100-32W-DN1-12F01-00	12W	typ.1800	typ.150	F1-F6	Y	D325 X H113	13.0kg	10pcs
BH100-32W-DN1-16F01-00	16W	typ.2400	typ.150	F1-F6	Y	D325 X H113	14.0kg	10pcs

Design Profile





MOD 270 BH120



MOD -D270 bulkheads widely use to replace the traditional 2D fluorescent light, The suitable dimension and various of function options make it very popular on the market. It can reach 120 LM/W to help you get a well energy saving.

Features

- > Up to 120 LM/W @1450LM
- > IP65 waterproof
- > UV-Anti
- > Various of function options
- > Warranty: 5 years

CCT

Single Color: 3000K, 4000K, 5000K, 6000K
Tri-color: 3000K, 4000K, 5000K, 6000K

Function

F1: ON/OFF
F2: ON/OFF + Emergency
F3: ON/OFF + MS
F4: ON/OFF + Emergency + MS
F5: ON/OFF + Self EM
F6: ON/OFF + Self EM + MS

Electrical Parameters

AC 200-240V, PF ≥0.95, THD <15%, Flicker Free

Photometric Parameters

100 LM/W, 120 LM/W, CRI>80 SDCM <5, LM79 TM-21, ERP2.0

IP Rating

IP65

Finish


White, Silver, Black

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Function	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
BH120-27W-KN1-10F01-00	10W	typ.1200	typ.120	F1-F6	Y	D270 X H113	11.0kg	10pcs
BH120-27W-KN1-12F01-00	12W	typ.1450	typ.120	F1-F6	Y	D270 X H113	11.0kg	10pcs



MOD 470 BH130



MOD -D470 bulkheads widely use to replace the traditional 2D fluorescent light, The suitable dimension and various of function options make it very popular on the market. It can reach 120 LM/W and 150 LM/W to help you get a well energy saving.

Features

- > Up to 150 LM/W@4500LM
- > IP65 waterproof
- > UV-Anti
- > Various of function options
- > Warranty: 5 years

CCT

Single Color: 3000K, 4000K, 5000K, 6000K
Tri-color: 3000K, 4000K, 5000K, 6000K

Function

F1: ON/OFF
F2: ON/OFF + Emergency
F3: ON/OFF + MS
F4: ON/OFF + Emergency + MS
F5: ON/OFF + Self EM
F6: ON/OFF + Self EM + MS

Electrical Parameters

AC 200-240V, PF ≥0.95, THD <15%, Flicker Free

Photometric Parameters

120 LM/W, 150 LM/W, CRI>80 SDCM <5, LM79 TM-21, ERP2.0

IP Rating

IP65

Finish


White, Silver, Black

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Function	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
BH130-47W-DN1-20F01-00	20W	typ.3000	typ.150	F1-F6	Y	D470 X H93	10.0kg	5pcs
BH130-47W-DN1-30F01-00	30W	typ.4500	typ.150	F1-F6	Y	D470 X H93	10.0kg	5pcs



Gamma BH200 | D295



Gamma is a smart design and functional bulkhead. Use the bracket for the surface mounting installation, AC terminal and functional switch in the case make the gamma very popular.

Features

- > Up to 130 LM/W@ 2100 LM
- > IP65 waterproof
- > UV-Anti
- > Various of function options
- > Warranty: 5 years

CCT Single Color 3000K 4000K 5000K 6000K Tri-color 2700K 3000K 3500K 4000K 5000K 6000K

Function F1: ON OFF F2: ON OFF + Emergency F3: ON OFF + MS F4: ON OFF + Emergency + MS F5: ON OFF + Self EM F6: ON OFF + Self EM + MS

Electrical Parameters AC 200-240V PF ≥ 0.95 THD $< 15\%$ Flicker Free

Photometric Parameters 100 LM/W 130 LM/W CRI > 80 SDCM < 5 LM79 TM-21 ERP2.0

IP Rating IP65


Finish White Silver Black

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Function	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
BH200-29W-ST1-12F01-00	12W	typ.1600	typ.130	F1-F6	Y	D295 X H57	12.6kg	10pcs
BH200-29W-ST1-16F01-00	16W	typ.2100	typ.130	F1-F6	Y	D295 X H57	12.6kg	10pcs



Gamma Mini BH210 | D250



Gamma Mini is a smart design and functional bulkhead. Use the bracket for the surface mounting installation, AC terminal and functional switch in the case make the gamma mini very popular.

Features

- > Up to 120 LM/W@ 1200 LM
- > IP65 waterproof
- > UV-Anti
- > Various of function options
- > Warranty: 5 years

CCT Single Color 3000K 4000K 5000K 6000K Tri-color 2700K 3000K 3500K 4000K 5000K 6000K

Function F1: ON OFF F2: ON OFF + Emergency F3: ON OFF + MS F4: ON OFF + Emergency + MS F5: ON OFF + Self EM F6: ON OFF + Self EM + MS

Electrical Parameters AC 200-240V PF ≥ 0.95 THD $< 15\%$ Flicker Free

Photometric Parameters 100 LM/W 120 LM/W CRI > 80 SDCM < 5 LM79 TM-21 ERP2.0

IP Rating IP65


Finish White Silver Black

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Function	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
BH210-25W-ST1-10F01-00	10W	typ.1200	Typ.120	F1-F6	Y	D250 X H50	12.5kg	10pcs



Pro R280 BH300



Pro is a 4 knock-out bulkhead, It is a IP65 and UV-Anti full with full plastic case.

The multiple function options make the Pro same as the other bulkhead which is widely used on the indoor and outdoor applications.

High technology LED makes the more higher lumem output

Features

- > Up to 150 LM/W@ 2400 LM
- > IP65 waterproof
- > UV-Anti
- > Various of function options
- > Warranty: 5 years

CCT

Single Color

3000K4000K5000K6000K

Tri-color

2700K3000K3500K4000K4500K5000K5500K6000K

Function

F1:

ON OFF

F2:

ON OFFEmergency

F3:

ON OFFMS

F4:

ON OFFEmergencyMS

F5:

ON OFFSelf EM

F6:

ON OFFSelf EMMS

Electrical Parameters

AC200-240V

PF≥0.95

THD<15%

Flicker Free

Photometric Parameters

120LM/W

150LM/W

CRI>80SDCM<5

LM79TM-21

ERP2.0

IP Rating

IP65

Finish

White

Silver


Black

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Function	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
BH300-28W-ST1-12F01-00	12W	typ.1800	Typ.150	F1-F6	Y	D280 X H85	12.0kg	10pcs
BH300-28W-ST1-16F01-00	16W	typ.2400	Typ.150	F1-F6	Y	D280 X H85	12.0kg	10pcs



Pro R320 BH320



Pro Series bulkheads be designed a function gear tray which be assembled together with PC cover as a assembly unit

The simple design makes our lamp very easy on the installation.

Features

- > Up to 130 LM/W@ 2600LM
- > IP65 waterproof
- > UV-Anti
- > Various of function options
- > Warranty: 5 years

CCT: Single Color (3000K, 4000K, 5000K, 6000K), Tri-color (2700K, 3000K, 3500K, 4000K, 4500K, 5000K, 5500K, 6000K)

Function:

- F1: ON/OFF
- F2: ON/OFF + Emergency
- F3: ON/OFF + MS
- F4: ON/OFF + Emergency + MS
- F5: ON/OFF + Self EM
- F6: ON/OFF + Self EM + MS

Electrical Parameters:

- AC 200-240V
- PF ≥0.95
- THD <15%
- Flicker Free

Photometric Parameters:

- 100 LM/W
- 130 LM/W
- CRI>80 SDCM <5
- LM79 TM-21
- ERP2.0

IP Rating: IP65


Finish: White, Black

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Function	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
BH320-32W-AT1-20F01-00	20W	typ.2600	typ.130	F1-F6	Y	D320 X H85	11.0kg	5pcs



Pro R320A BH321



Pro Series bulkheads be designed a function gear tray which be assembled together with PC cover as a assembly unit

The simple design makes our lamp very easy on the installation.

Features

- > Up to 130 LM/W@ 2600LM
- > IP65 waterproof
- > UV-Anti
- > Various of function options
- > Warranty: 5 years

CCT: Single Color (3000K, 4000K, 5000K, 6000K), Tri-color (2700K, 3000K, 3500K, 4000K, 4500K, 5000K, 5500K, 6000K)

Function:

- F1: ON/OFF
- F2: ON/OFF + Emergency
- F3: ON/OFF + MS
- F4: ON/OFF + Emergency + MS
- F5: ON/OFF + Self EM
- F6: ON/OFF + Self EM + MS

Electrical Parameters:

- AC 200-240V
- PF ≥0.95
- THD <15%
- Flicker Free

Photometric Parameters:

- 130 LM/W
- CRI>80 SDCM <5
- LM79 TM-21
- ERP2.0

IP Rating: IP65


Finish: White, Black

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Function	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
BH321-32W-AT1-20F01-00	20W	typ.2600	typ.130	F1-F6	Y	D320 X H85	13kg	5pcs



Pro S320 BH330



Pro Series bulkheads be designed a function gear tray which be assembled together with PC cover as a assembly unit

The simple design makes our lamp very easy on the installation.

Features

- > Up to 130 LM/W@ 2600LM
- > IP65 waterproof
- > UV-Anti
- > Various of function options
- > Warranty: 5 years

CCT: Single Color (3000K, 4000K, 5000K, 6000K), Tri-color (2700K, 3000K, 3500K, 4000K, 4500K, 5000K, 5500K, 6000K)

Function:

- F1: ON/OFF
- F2: ON/OFF + Emergency
- F3: ON/OFF + MS
- F4: ON/OFF + Emergency + MS
- F5: ON/OFF + Self EM
- F6: ON/OFF + Self EM + MS

Electrical Parameters:

- AC 200-240V
- PF ≥0.95
- THD <15%
- Flicker Free

Photometric Parameters:

- 100 LM/W
- 130 LM/W
- CRI>80 SDCM <5
- LM79 TM-21
- ERP2.0

IP Rating: IP65


Finish: White, Black

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Function	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
BH330-32W-AT1-20F01-00	20W	typ.2600	typ.130	F1-F6	Y	D320 X H85	11.0kg	5pcs



Pro S320A BH331



Pro Series bulkheads be designed a function gear tray which be assembled together with PC cover as a assembly unit

The simple design makes our lamp very easy on the installation.

Features

- > Up to 130 LM/W@ 2600LM
- > IP65 waterproof
- > UV-Anti
- > Various of function options
- > Warranty: 5 years

CCT: Single Color (3000K, 4000K, 5000K, 6000K), Tri-color (2700K, 3000K, 3500K, 4000K, 4500K, 5000K, 5500K, 6000K)

Function:

- F1: ON/OFF
- F2: ON/OFF + Emergency
- F3: ON/OFF + MS
- F4: ON/OFF + Emergency + MS
- F5: ON/OFF + Self EM
- F6: ON/OFF + Self EM + MS

Electrical Parameters:

- AC 200-240V
- PF ≥0.95
- THD <15%
- Flicker Free

Photometric Parameters:

- 130 LM/W
- CRI>80 SDCM <5
- LM79 TM-21
- ERP2.0

IP Rating: IP65

Finish: White, Black

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Function	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
BH331-20W-AT1-20F01-00	20W	typ.2600	typ.130	F1-F6	Y	D320 X H85	13kg	5pcs




BH420



BH421

Lunar D350

BH420 | Die-cast



Lunar is die-cast bulkhead with full and half moon cover,
It is widely used at outdoor applications due to the IP65 /
UV-anti / Aluminum case as heating sink.
Easy quick installation - wall or ceiling mounted.
High technology LED provide a more higher lumen output.

Features

- > UP to 150LM/W@4500LM
- > Die-cast Aluminum case as heating sink
- > IP65 waterproof & UV-Anti
- > 5 years warranty

CCT

Single Color: 3000K, 4000K, 5000K, 6000K
Tri-color: 3000K, 4000K, 5000K

Function

F1: ON/OFF
F2: ON/OFF + Emergency
F3: ON/OFF + MS
F4: ON/OFF + Emergency + MS
F5: ON/OFF + Self EM
F6: ON/OFF + Self EM + MS

Electrical Parameters

AC 200-240V, PF ≥0.95, THD <15%, Flicker Free

Photometric Parameters

120 LM/W, 150 LM/W, CRI>80 SDCM <5, LM79 TM-21, ERP2.0

IP Rating

IP65

Finish

White, Gray, Black

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Function	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
BH420-35W-DT1-20F01-00	20W	typ.3000	typ.150	F1-F6	Y	D350 X H107	12.0kg	4pcs
BH420-35W-DT1-30F01-00	30W	typ.4500	typ.150	F1-F6	Y	D350 X H107	12.0kg	4pcs



BH410



BH411




BH400



BH401

Lunar D275


BH410 | Die-cast



Lunar is die-cast bulkhead with full and half moon cover,
It is widely used at outdoor applications due to the IP65 /
UV-anti / Aluminum case as heating sink.
Easy quick installation - wall or ceiling mounted.
High technology LED provide a more higher lumen output.

Features

- > UP to 130LM/W@2100LM
- > Die-cast Aluminum case as heating sink
- > IP65 waterproof & UV-Anti
- > 5 years warranty



Electrical Parameters



Photometric Parameters



IP Rating



Finish




Data Sheet

Order Code	Rated Power	Lumen	LM/W	Function	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
BH410-27W-DT1-12F01-00	12W	typ.1500	typ.130	F1-F6	Y	D275 X H80	11.0kg	5pcs
BH410-27W-DT1-16F01-00	16W	typ.2100	typ.130	F1-F6	Y	D275 X H80	11.0kg	5pcs

Lunar D220


BH400 | Die-cast



Lunar is die-cast bulkhead with full and half moon cover,
It is widely used at outdoor applications due to the IP65 /
UV-anti / Aluminum case as heating sink.
Easy quick installation - wall or ceiling mounted.
High technology LED provide a more higher lumen output.

Features

- > UP to 100LM/W@1000LM
- > Die-cast Aluminum case as heating sink
- > IP65 waterproof & UV-Anti
- > 5 years warranty



Electrical Parameters



Photometric Parameters



IP Rating



Finish



Data Sheet

Order Code	Rated Power	Lumen	LM/W	Function	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
BH400-22W-DT1-10F01-00	10W	typ.1000	typ.100	F1-F6	Y	D222 X H66	11.0kg	10pcs



PC cover + gear tray assembly
with functional module

Standard ON/OFF
Standard+ 3h Emergency
Standard+ Microwave
Standard+ 3h Emergency + Microwave



installation bottom plastic case

LiFePO4 -IRON BATTERIES -3 hours
Emergency Operation



Waterproof gasket



1-10v Dimming/DALI Driver


Plastic outer ring

The plastic outer ring provide the white
and black color with 4 knock-out clips



Astro

BH500 | S260



Astro series bulkheads be designed a function gear tray which be assembled together with PC cover as a assembly unit

The 4 knock-out clips on the middle rings makes the Astro very easy on the installation

Features

- > Up to 130 LM/W@ 2600LM
- > IP65 waterproof
- > UV-Anti
- > Various of function options
- > Warranty: 5 years

CCT: Single Color (3000K, 4000K, 5000K, 6000K), Tri-color (2700K, 3000K, 3500K, 4000K, 4500K, 5000K, 5500K, 6000K)

Function: F1: ON/OFF, F2: ON/OFF + Emergency, F3: ON/OFF + MS, F4: ON/OFF + Emergency + MS, F5: ON/OFF + Self EM, F6: ON/OFF + Self EM + MS

Electrical Parameters: AC 200-240V, PF ≥0.95, THD <15%, Flicker Free

Photometric Parameters: 100 LM/W, 130 LM/W, CRI>80 SDCM <5, LM79 TM-21, ERP2.0

IP Rating: IP65

Finish: White, Black


Data Sheet

Order Code	Rated Power	Lumen	LM/W	Function	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
BH500-26W-AT1-14F10-00	7-14W	typ.900-1800	typ.130	F1-F6	Y	D263 X H74	11.0kg	5pcs



Astro Mini

BH510 | S200



Astro series bulkheads be designed a function gear tray which be assembled together with PC cover as a assembly unit

The 4 knock-out clips on the middle rings makes the Astro very easy on the installation

Features

- > Up to 120 LM/W@ 1680LM
- > IP65 waterproof
- > UV-Anti
- > Various of function options
- > Warranty: 5 years

CCT: Single Color (3000K, 4000K, 5000K, 6000K), Tri-color (2700K, 3000K, 3500K, 4000K, 4500K, 5000K, 5500K, 6000K)

Function: F1: ON/OFF, F2: ON/OFF + Emergency, F3: ON/OFF + MS, F4: ON/OFF + Emergency + MS, F5: ON/OFF + Self EM, F6: ON/OFF + Self EM + MS

Electrical Parameters: AC 200-240V, PF ≥0.95, THD <15%, Flicker Free

Photometric Parameters: 100 LM/W, CRI>80 SDCM <5, LM79 TM-21, ERP2.0

IP Rating: IP65


Finish: White, Black

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Function	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
BH510-20W-AT1-07F10-00	3.5-7W	typ.420-840	typ.120	F1-F6	Y	D200 X H65	9.7kg	5pcs



Delta
BH520 | R290



Delta series bulkheads be designed a function gear tray which be assembled together with PC cover as a assembly unit

The 4 knock-out clips on the middle rings makes the Astro very easy on the installation

- Features
- > Up to 130 LM/W@ 2600LM
 - > IP65 waterproof
 - > UV-Anti
 - > Various of function options
 - > Warranty: 5 years

CCT Single Color 3000K 4000K 5000K 6000K Tri-color 2700K 3000K 3500K 4000K 5000K 6000K

Function

F1: ON OFF F2: ON OFF + Emergency F3: ON OFF + MS F4: ON OFF + Emergency + MS F5: ON OFF + Self EM F6: ON OFF + Self EM + MS

Electrical Parameters

AC 200-240V PF ≥0.95 THD <15% Flicker Free

Photometric Parameters

100 LM/W 130 LM/W CRI>80 SDCM <5 LM79 TM-21 ERP2.0

IP Rating

IP65

Finish


White Black

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Function	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
BH520-29W-AT1-14F10-00	7-14W	typ.900-1800	typ.130	F1-F6	Y	D290 X H74	11.0kg	5pcs



Delta Mini
BH530 | R200



Delta series bulkheads be designed a function gear tray which be assembled together with PC cover as a assembly unit

The 4 knock-out clips on the middle rings makes the Astro very easy on the installation

- Features
- > Up to 120 LM/W@ 1680LM
 - > IP65 waterproof
 - > UV-Anti
 - > Various of function options
 - > Warranty: 5 years

CCT Single Color 3000K 4000K 5000K 6000K Tri-color 2700K 3000K 3500K 4000K 5000K 6000K

Function

F1: ON OFF F2: ON OFF + Emergency F3: ON OFF + MS F4: ON OFF + Emergency + MS F5: ON OFF + Self EM F6: ON OFF + Self EM + MS

Electrical Parameters

AC 200-240V PF ≥0.95 THD <15% Flicker Free

Photometric Parameters

100 LM/W CRI>80 SDCM <5 LM79 TM-21 ERP2.0

IP Rating

IP65

Finish

White Black


Data Sheet

Order Code	Rated Power	Lumen	LM/W	Function	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
BH530-20W-AT1-07F10-00	3.5-7W	typ.420-840	typ.120	F1-F6	Y	D200 X H65	9.7kg	5pcs



Wall Pack

WP100




The LED Wall Pack Light is great for commercial and security lighting purposes where the light will need to operate for long periods of time. Their bright light output and adjustable mount design make them an ideal choice for illuminating building perimeters where control of spill light is important.

Features

- > Various of functions for options
- > High lumen output at 130LM/W
- > Surge protection: L/N-PE: 5kV, L-N: 5kV
- > Easy Installation
- > Flicker free
- > 5 years warranty

CCT



Function



Electrical Parameters



Photometric Parameters



IP/IK




Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
WP100-36B-AN1-50F01-00	50W	typ.6500	typ.130	Y	L363 X W235 X H196	2.8kg	1pcs
WP100-36B-AN1-75F01-00	75W	typ.9750	typ.130	Y	L363 X W235 X H196	3.4kg	1pcs
WP100-36B-AN1-1BF01-00	100W	typ.13000	typ.130	Y	L363 X W235 X H196	3.7kg	1pcs



Wall Pack

WP200




The LED Wall Pack Light is great for commercial and security lighting purposes where the light will need to operate for long periods of time. Their bright light output and adjustable mount design make them an ideal choice for illuminating building perimeters where control of spill light is important.

Features

- > Various of functions for options
- > High lumen output at 130LM/W
- > Surge protection: L/N-PE: 5kV, L-N: 5kV
- > Easy Installation
- > Flicker free
- > 5 years warranty

CCT



Function



Electrical Parameters



Photometric Parameters



IP/IK




Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
WP200-30B-AN1-40F01-00	40W	typ.5200	typ.130	Y	L308 X W265 X H182	2.8kg	1pcs





Vasco R350A CL100



Vasco series is a low glare/UGR<19 and IP20 ceiling light the classic round shape is simple and elegant, the low-glare lighting design makes it suitable for a variety of indoor applications
120LM/W and UGR<19 features make the more and more client interest in the vasco ceiling light

Features

- > Up to 120 LM/W@ 3600LM
- > Aluminum round shape + Prismatic diffuser UGR<19
- > Junction box for easy installation
- > Various of function options
- > Warranty: 5 years

CCT: Single Color (3000K, 4000K, 5000K, 6000K) Tri-color (2700K, 3000K, 3500K, 4000K, 4500K, 5000K, 5500K, 6000K)

Function: F1: ON/OFF, F2: ON/OFF + Emergency, F3: ON/OFF + MS, F4: ON/OFF + Emergency + MS, F5: ON/OFF + Self EM, F6: ON/OFF + Self EM + MS

Electrical Parameters: AC 200-240V, PF ≥0.95, THD <15%, Flicker Free

Photometric Parameters: 100 LM/W, 120 LM/W, CRI>80 SDCM <5, LM79 TM-21, ERP2.0

IP Rating: IP20

Finish: White, Black


Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	UP Light	Dimension (mm)	GW/CTN	QTY/CTN
CL100-35W-KT1-20F01-00	20W	typ.2400	typ.120	Y	N	D350xH80	14kg	5pcs
CL101-35W-KT1-20F01-00	20W	typ.2400	typ.120	Y	Y	D350xH80	14kg	5pcs



Vasco R450A

CL110



Vasco series is a low glare/UGR<19 and IP20 ceiling light the classic round shape is simple and elegant, the low-glare lighting design makes it suitable for a variety of indoor applications
120LM/W and UGR<19 features make the more and more client interest in the vasco ceiling light


Features

- > Up to 120 LM/W@ 3600LM
- > Aluminum round shape + Prismatic diffuser UGR<19
- > Junction box for easy installation
- > Various of function options
- > Warranty: 5 years

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	UP Light	Dimension (mm)	GW/CTN	QTY/CTN
CL110-45W-KT1-30F01-00	30W	typ.3600	typ.120	Y	N	D450xH80	17kg	5pcs
CL111-45W-KT1-30F01-00	30W	typ.3600	typ.120	Y	Y	D450xH80	17kg	5pcs

CCT



Function



Electrical Parameters



Photometric Parameters



IP Rating




Finish



Vasco R600A

CL120



Vasco series is a low glare/UGR<19 and IP20 ceiling light the classic round shape is simple and elegant, the low-glare lighting design makes it suitable for a variety of indoor applications
120LM/W and UGR<19 features make the more and more client interest in the vasco ceiling light


Features

- > Up to 120 LM/W@ 6000LM
- > Aluminum round shape + Prismatic diffuser UGR<19
- > Junction box for easy installation
- > Various of function options
- > Warranty: 5 years


Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	UP Light	Dimension (mm)	GW/CTN	QTY/CTN
CL120-60W-KT1-50F01-00	50W	typ.6000	typ.120	Y	N	D600xH90	5.8kg	1pcs
CL121-60W-KT1-50F01-00	50W	typ.6000	typ.120	Y	Y	D600xH90	5.8kg	1pcs

CCT



Function



Electrical Parameters



Photometric Parameters



IP Rating




Finish





Vasco R900A CL130



Vasco series is a low glare/UGR<19 and IP20 ceiling light the classic round shape is simple and elegant, the low-glare lighting design makes it suitable for a variety of indoor applications

120LM/W and UGR<19 features make the more and more client interest in the vasco ceiling light

Features

- > Up to 120 LM/W@ 8160LM
- > Aluminum round shape + Prismatic diffuser UGR<19
- > Junction box for easy installation
- > Various of function options
- > Warranty: 5 years

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	UP Light	Dimension (mm)	GW/CTN	QTY/CTN
CL130-90W-KT1-68F01-00	68W	typ.8160	typ.120	Y	N	D900xH90	7kg	1pcs
CL131-90W-KT1-68F01-00	68W	typ.8160	typ.120	Y	Y	D900xH90	7kg	1pcs



Electrical Parameters




Photometric Parameters



IP Rating



Finish



Prismatic

Eye Protection
Anti-Glare

UGR<19 Low Glare

No Flicker, No noise

PCB + LED + Metal plate assembly

PS diffuser as the light guide

Prismatic diffuser for UGR<19

Aluminum outer ring


The aluminum outer ring provide the white and black color

Installation junction
with functional module

Standard ON/OFF
Standard+ 3h Emergency
Standard+ Microwave
Standard+ 3h Emergency + Microwave



LEO R355A CL200



Leo series is an IP20 ceiling for indoor use, It use the aluminum case as heat sink and easy installation.
130LM/W output make the LEO ceiling light widely use on various of indoor applications .

Features

- > Up to 130 LM/W@ 3600LM
- > Aluminum housing + PC cover
- > Various of function options
- > Warranty: 5 years

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
CL200-35W-KT1-20F01-00	20W	typ.3600	typ.130	Y	D355xH100	10.5kg	10pcs
CL200-35W-KT1-30F01-00	30W	typ.3900	typ.130	Y	D355xH100	10.5kg	10pcs



CCT

Single Color: 3000K, 4000K, 5000K, 6000K
Tri-color: 3000K, 4000K, 5000K, 6000K

Function

F1: ON/OFF
F2: ON/OFF + Emergency
F3: ON/OFF + MS
F4: ON/OFF + Emergency + MS
F5: ON/OFF + Self EM
F6: ON/OFF + Self EM + MS

Electrical Parameters

AC 200-240V, PF ≥0.95, THD <15%, Flicker Free

Photometric Parameters

100 LM/W, 130 LM/W, CRI>80 SDCM <5, LM79 TM-21, ERP2.0

IP Rating


IP20

Finish

White, Black



LEO R435A CL210




Leo series is an IP20 ceiling for indoor use, It use the aluminum case as heat sink and easy installation. 130LM/W output make the LEO ceiling light widely use on various of indoor applications .

Features

- > Up to 130 LM/W@ 3900LM
- > Aluminum housing + PC cover
- > Various of function options
- > Warranty: 5 years

CCT



Function



Electrical Parameters



Photometric Parameters



IP Rating




Finish



Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
CL210-43W-KT1-20F01-00	20W	typ.3600	typ.130	Y	D435xH100	12kg	5pcs
CL210-43W-KT1-30F01-00	30W	typ.3900	typ.130	Y	D435xH100	12kg	5pcs




Aluminum bottom case

Aluminum case with the clips inside to support the gear tray installation

Polycarbonate Cover

Made from virgin polycarbonate achieving high transmittance of 80% and vandal resistance rating of IK08.




Multifunctional Gear Tray

Standard ON/OFF
Standard+ 3h Emergency
Standard+ Microwave
Standard+ 3h Emergency + Microwave



Backlit Panel

PN100 | HB | UGR>19



PN100 Back-lit Panel light is a direct lighting with external driver, adopts SMD led with optical lens to provide a uniform light effect, no LGP design makes the panel light more cost effective, high lumen efficiency available with 105lm/w, 120lm/w, 140lm/w, 160lm/w. Recessed, suspended, and surface mounted installation available.

- Features
 - > Ultra flat casing: 32mm
 - > Up to 160lm/w@8000LM
 - > White frame color: RAL9016
 - > Flicker free & 5 years warranty

► CCT

- Single Color
 - 3000K
 - 4000K
 - 5000K
 - 6000K
- Tri-color
 - 2700K
 - 3000K
 - 3500K
 - 4000K
 - 5000K
 - 6000K

► Function

- ON OFF
- 1-10V Dimming
- DALI
- Emergency

► Electrical Parameters

- AC 200-240V
- PF ≥0.95
- THD <15%
- Flicker Free

► Photometric Parameters

- 105/120 LM/W
- 140/160 LM/W
- CRI>80 SDCM <5
- LM79 TM-21
- ERP2.0

► Installation

- Recessed
- Surface Mounted
- Suspension

► IP Rating

- IP20
- IP44

► Data Sheet


Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
PN100-22W-SN1-30F01-00	30W	typ.4800	typ.160	Y	L595 X W595 X H32	24.0kg	10pcs
PN100-41W-SN1-30F01-00	30W	typ.4200	typ.140	Y	L1195 X W295 X H32	12.0kg	5pcs
PN100-42W-SN1-50F01-00	50W	typ.8000	typ.160	Y	L1195 X W595 X H32	24.0kg	5pcs
PN100-62W-SN1-30F01-00	30W	typ.4800	typ.160	Y	L620 X W620 X H32	24.5kg	10pcs



Prismatic

Backlit Panel

PN110 | TP(b) | UGR>19



PN110 Back-lit Panel light is a direct lighting with TP(b) fire rated, adopts SMD led with optical lens to provide a uniform light effect, no LGP design makes the panel light more cost effective, high lumen efficiency available with 105lm/w, 120lm/w, 140lm/w, 160lm/w. Recessed, suspended, and surface mounted installation available.

Features

- > Ultra flat casing: 32mm
- > Up to 160lm/w@8000LM
- > White frame color: RAL9016
- > Flicker free & 5 years warranty

CCT Single Color 3000K 4000K 5000K 6000K Tri-color 2700K 3000K 3500K 4000K 4500K 5000K 5500K 6000K

Function ON OFF 1-10V Dimming DALI Emergency TP(b)

Electrical Parameters AC 200-240V PF ≥0.95 THD <15% Flicker Free

Photometric Parameters 105/120 LM/W 140/160 LM/W CRI>80 SDCM <5 LM79 TM-21 ERP2.0

Installation Recessed Surface Mounted Suspension


IP Rating IP20 IP44

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
PN110-22W-SN1-30F01-00	30W	typ.4800	typ.160	Y	L595 X W595 X H32	24.0kg	10pcs
PN110-41W-SN1-30F01-00	30W	typ.4200	typ.140	Y	L1195 X W295 X H32	12.0kg	5pcs
PN110-42W-SN1-50F01-00	50W	typ.8000	typ.160	Y	L1195 X W595 X H32	24.0kg	5pcs
PN110-62W-SN1-30F01-00	30W	typ.4800	typ.160	Y	L620 X W620 X H32	24.5kg	10pcs

Backlit Panel

PN120 | HB | UGR<19



PN120 Back-lit Panel light is a direct lighting with low glare UGR<19, adopts SMD led with optical lens to provide a uniform light effect, no LGP design makes the panel light more cost effective, high lumen efficiency available with 105lm/w, 120lm/w, 140lm/w, 150lm/w. Recessed, suspended, and surface mounted installation available.

Features

- > Ultra flat casing: 32mm
- > Up to 150lm/w@7500LM, UGR<19
- > White frame color: RAL9016
- > Flicker free & 5 years warranty

CCT Single Color 3000K 4000K 5000K 6000K Tri-color 2700K 3000K 3500K 4000K 4500K 5000K 5500K 6000K

Function ON OFF 1-10V Dimming DALI Emergency

Electrical Parameters AC 200-240V PF ≥0.95 THD <15% Flicker Free

Photometric Parameters 105/120 LM/W 140/150 LM/W CRI>80 SDCM <5 LM79 TM-21 ERP2.0 UGR <19

Installation Recessed Surface Mounted Suspension

IP Rating IP20 IP44


Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
PN120-22W-SN1-30F01-00	30W	typ.4500	typ.150	Y	L595 X W595 X H32	24.0kg	10pcs
PN120-41W-SN1-30F01-00	30W	typ.4200	typ.140	Y	L1195 X W295 X H32	12.0kg	5pcs
PN120-42W-SN1-50F01-00	50W	typ.7500	typ.150	Y	L1195 X W595 X H32	24.0kg	5pcs
PN120-62W-SN1-30F01-00	30W	typ.4500	typ.150	Y	L620 X W620 X H32	24.5kg	10pcs



Backlit Panel

PN130 | TP(b) | UGR<19



PN130 Back-lit Panel light is a direct lighting with low glare UGR<19, TP(b) fire rated, adopts SMD led with optical lens to provide a uniform light effect, no LGP design makes the panel light more cost effective, high lumen efficiency available with 105lm/w, 120lm/w, 140lm/w, 150lm/w. Recessed, suspended, and surface mounted installation available.

Features

- > Ultra flat casing: 32mm
- > Up to 150lm/w@7500LM, UGR<19, TP(b)
- > White frame color: RAL9016
- > Flicker free & 5 years warranty


Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
PN130-22W-SN1-30F01-00	30W	typ.4500	typ.150	Y	L595 X W595 X H32	24.0kg	10pcs
PN130-41W-SN1-30F01-00	30W	typ.4200	typ.140	Y	L1195 X W295 X H32	12.0kg	5pcs
PN130-52W-SN1-50F01-00	50W	typ.7500	typ.150	Y	L1195 X W595 X H32	24.0kg	5pcs
PN130-62W-SN1-30F01-00	30W	typ.4500	typ.150	Y	L620 X W620 X H32	24.5kg	10pcs



Backlit Panel

PN140 | TP(a) | UGR<19



PN140 Back-lit Panel light is a direct lighting with low glare UGR<19, TP(a) fire rated, adopts SMD led with optical lens to provide a uniform light effect, no LGP design makes the panel light more cost effective, high lumen efficiency available with 105lm/w, 120lm/w, 140lm/w, 150lm/w. Recessed, suspended, and surface mounted installation available.

Features

- > Ultra flat casing: 32mm
- > Up to 150lm/w@7500LM, UGR<19, TP(a)
- > White frame color: RAL9016
- > Flicker free & 5 years warranty


Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
PN140-22W-SN1-30F01-00	30W	typ.4500	typ.150	Y	L595 X W595 X H32	24.0kg	10pcs
PN140-41W-SN1-30F01-00	30W	typ.4200	typ.140	Y	L1195 X W295 X H32	12.0kg	5pcs
PN140-42W-SN1-50F01-00	50W	typ.7500	typ.150	Y	L1195 X W595 X H32	24.0kg	5pcs
PN140-62W-SN1-30F01-00	30W	typ.4500	typ.150	Y	L620 X W620 X H32	24.5kg	10pcs



Backlit Panel

PN150 | TP(a) | UGR>19



PN150 Back-lit Panel light is a direct lighting with, TP(a) fire rated, adopts SMD led with optical lens to provide a uniform light effect, no LGP design makes the panel light more cost effective, high lumen efficiency available with 105lm/w, 120lm/w, 150lm/w, 160lm/w. Recessed, suspended, and surface mounted installation available.

Features

- > Ultra flat casing: 32mm
- > Up to 160lm/w@8000LM, TP(a)
- > White frame color: RAL9016
- > Flicker free & 5 years warranty

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
PN150-22W-SN1-30F01-00	30W	typ.4800	typ.160	Y	L595 X W595 X H32	24.0kg	10pcs
PN150-41W-SN1-30F01-00	30W	typ.4500	typ.150	Y	L1195 X W295 X H32	12.0kg	5pcs
PN150-42W-SN1-50F01-00	50W	typ.8000	typ.160	Y	L1195 X W595 X H32	24.0kg	5pcs
PN150-62W-SN1-30F01-00	30W	typ.4800	typ.160	Y	L620 X W620 X H32	24.5kg	10pcs

CCT

Single Color

3000K4000K5000K6000K

Tri-color

Function

ON OFF

1-10V Dimming

DALI

Emergency

TP(a)

Electrical Parameters

AC200-240V

PF≥0.95

THD<15%

Flicker Free

Photometric Parameters

105/120 LM/W

150/160 LM/W

CRI>80SDCM<5

LM79 TM-21

ERP2.0

Installation

Recessed

Surface Mounted

Suspension

IP Rating

IP20


IP44





Edgelit Panel

PN200 | HB | UGR>19



PN200 Edge-lit panel is a effective cost panel .PMMA LGP produce uniform light high lumen output up to 140LM/W,It can fit seamlessly into any work place, It is available in recessed, suspended and surface mounted installation method. It makes the panels were widely use on various of applications

Features

- > Suitably efficient - up to 140 LM/W
- > High Luminous flux - up to 7000 lm
- > PMMA LGP as light guide
- > Extra thin aluminum frame
- > 5 years warranty

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
PN200-22W-SN1-30F01-00	30W	typ.4200	typ.140	Y	L595 X W595 X H10	13.0kg	4pcs
PN200-41W-SN1-30F01-00	30W	typ.3900	typ.130	Y	L1195 X W295 X H10	16.5kg	5pcs
PN200-42W-SN1-50F01-00	50W	typ.7000	typ.140	Y	L1195 X W595 X H10	12.0kg	2pcs
PN200-62W-SN1-30F01-00	30W	typ.4200	typ.140	Y	L620 X W620 X H10	16.0kg	4pcs



Prismatic

Edgelit Panel

PN210 | HB | UGR<19



PN210 Edge-lit panel is Non fire rated low glare panel up to 140LM/W. The comfortable light and high color consistency for various of applications .

It is available in recessed, suspended and surface mounted installation method. It makes the panels were widely use on various of applications

Features

- > Prismatic UGR<19
- > Suitably efficient - up to 140 LM/W
- > High Luminous flux - up to 7000 lm
- > PMMA LGP as light guide
- > Extra thin aluminum frame
- > 5 years warranty

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
PN210-22W-SN1-30F01-00	30W	typ.4200	typ.140	Y	L595 X W595 X H10	13.0kg	4pcs
PN210-41W-SN1-30F01-00	30W	typ.3900	typ.130	Y	L1195 X W295 X H10	16.5kg	5pcs
PN210-42W-SN1-50F01-00	50W	typ.7000	typ.140	Y	L1195 X W595 X H10	12.0kg	2pcs
PN210-62W-SN1-30F01-00	30W	typ.4200	typ.140	Y	L620 X W620 X H10	16.0kg	4pcs

CCT

Single Color

Tri-color

Function

Electrical Parameters

Photometric Parameters

Installation

IP Rating

CCT

Single Color

Tri-color


Function

Electrical Parameters

Photometric Parameters


Installation

IP Rating



Edgelit Panel

PN220 | TP(b) | UGR>19



PN220 Edge-lit panel is TP(b) and low glare panel PMMA LGP produce uniform light high lumen up to 140LM/W.


The panels are available in recessed, suspended and surface mounted installation, it makes the panels were widely use on various of applications.

Features

- > TP(b) fire rated
- > Suitably efficient - up to 140 LM/W
- > High Luminous flux - up to 7000 lm
- > PMMA LGP as light guide
- > Extra thin aluminum frame
- > 5 years warranty

Data Sheet


Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
PN220-22W-SN1-30F01-00	30W	typ.4200	typ.140	Y	L595 X W595 X H10	13.0kg	4pcs
PN220-41W-SN1-30F01-00	30W	typ.3900	typ.130	Y	L1195 X W295 X H10	16.5kg	5pcs
PN220-42W-SN1-50F01-00	50W	typ.7000	typ.140	Y	L1195 X W595 X H10	12.0kg	2pcs
PN220-62W-SN1-30F01-00	30W	typ.4200	typ.140	Y	L620 X W620 X H10	16.0kg	4pcs



Prismatic

Edgelit Panel

PN230 | TP(b) | UGR<19



PN230 Edge-lit panel is a TP(b) and low glare panel up to 140LM/W. It is perfect for use in commercial buildings and environments.


It is available in recessed, suspended and surface mounted installation method. It makes the panels were widely use on various of applications


Features

- > Suitably efficient - up to 140 LM/W
- > High Luminous flux - up to 7000 lm
- > PMMA LGP as light guide
- > Prismatic UGR<19, TP(b) fire-proof
- > Extra thin aluminum frame
- > 5 years warranty

Data Sheet


Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
PN230-22W-SN1-30F01-00	30W	typ.4200	typ.140	Y	L595 X W595 X H10	13.0kg	4pcs
PN230-41W-SN1-30F01-00	30W	typ.3900	typ.130	Y	L1195 X W295 X H10	16.5kg	5pcs
PN230-42W-SN1-50F01-00	50W	typ.7000	typ.140	Y	L1195 X W595 X H10	12.0kg	2pcs
PN230-62W-SN1-30F01-00	30W	typ.4200	typ.140	Y	L620 X W620 X H10	16.0kg	4pcs





Edgelit Panel

PN240 | TP(a) | UGR>19



PN240 Edge-lit panel is a TP(a) fire rated panel, It is an energy savings solution with up to 140 lm/W lumen output.

The panels are available in recessed, suspended and surface mounted installation, it makes the panels were widely use on various of applications.

Features

- > TP(a) fire-proof
- > Suitably efficient - up to 140 LM/W
- > High Luminous flux - up to 7000 lm
- > PMMA LGP as light guide
- > Extra thin aluminum frame
- > 5 years warranty

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
PN240-22W-SN1-30F01-00	30W	typ.4200	typ.140	Y	L595 X W595 X H10	13.0kg	4pcs
PN240-41W-SN1-30F01-00	30W	typ.3900	typ.130	Y	L1195 X W295 X H10	16.5kg	5pcs
PN240-42W-SN1-50F01-00	50W	typ.7000	typ.140	Y	L1195 X W595 X H10	12.0kg	2pcs
PN240-62W-SN1-30F01-00	30W	typ.4200	typ.140	Y	L620 X W620 X H10	16.0kg	4pcs



CCT Single Color 3000K 4000K 5000K 6000K Tri-color

Function ON/OFF 1-10V Dimming DALI Emergency TP(a)

Electrical Parameters AC 200-240V PF ≥0.95 THD <15% Flicker Free

Photometric Parameters 105/120 LM/W 130/140 LM/W CRI>80 SDCM <5 LM79 TM-21 ERP2.0

Installation Recessed Surface Mounted Suspension


IP Rating IP20



Prismatic

Edgelit Panel

PN250 | TP(a) | UGR<19



PN250 Edge-lit panel is a high end technology with TP(a) fire rated and Low glare . It is up to 140 lm/W lumen output, The various of installation method and professional features make this panel were widely use on office, schools, meeting rooms and commercial applications.

Features

- > Prismatic UGR<19
- > TP(a) fire-proof
- > Suitably efficient - up to 140 LM/W
- > High Luminous flux - up to 7000 lm
- > PMMA LGP as light guide
- > Extra thin aluminum frame
- > 5 years warranty

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
PN250-22W-SN1-30F01-00	30W	typ.4200	typ.140	Y	L595 X W595 X H10	13.0kg	4pcs
PN250-41W-SN1-30F01-00	30W	typ.3900	typ.130	Y	L1195 X W295 X H10	16.5kg	5pcs
PN250-42W-SN1-50F01-00	50W	typ.7000	typ.140	Y	L1195 X W595 X H10	12.0kg	2pcs
PN250-62W-SN1-30F01-00	30W	typ.4200	typ.140	Y	L620 X W620 X H10	16.0kg	4pcs



CCT Single Color 3000K 4000K 5000K 6000K Tri-color

Function ON/OFF 1-10V Dimming DALI Emergency TP(a)

Electrical Parameters AC 200-240V PF ≥0.95 THD <15% Flicker Free

Photometric Parameters 105/120 LM/W 130/140 LM/W CRI>80 SDCM <5 LM79 TM-21 ERP2.0 UGR <19


Installation Recessed Surface Mounted Suspension

IP Rating IP20



Air Handling Panel

PN300 | TP(a) | UGR<19



Air Handling Panel Light is not only looks clean and pleasing but also result in visual comfort and good feeling for employees in the offices. Heat transfer, which's important to lighting lifespan, remains efficient due to excellent air-handling and air return over entire space. In a office ventilated with good air quality and provided with excellent thermal comfort, the employees will feel more satisfied and happier, playing an crucial role in productivity and positivity.


Features

- > Up to 140lm/w
- > Special design for air handling
- > Prismatic UGR<19
- > PMMA LGP
- > 5 years warranty

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
PN300-21W-SN1-20F01-00	20W	typ.2400	typ.120	Y	L595 X W295 X H25	24.0kg	10pcs
PN300-22W-SN1-32F01-00	32W	typ.4480	typ.140	Y	L595 X W595 X H25	21.0kg	5pcs
PN300-41W-SN1-32F01-00	32W	typ.4480	typ.140	Y	L1195 X W295 X H25	21.0kg	5pcs
PN300-42W-SN1-50F01-00	50W	typ.7000	typ.140	Y	L1195 X W595 X H25	44.0kg	5pcs

CCT



Function



Electrical Parameters



Photometric Parameters



Installation



IP Rating





Finish



Upscale Panel


PN400



Upscale Panel light is a low UGR suspended up & down panel constructed from Aluminium and rated to IP20. The fitting comes with an integral driver. Colour consistency is adhered to with a 3-Step MacAdams Ellipse binning strategy alongside an LED chipset at CRI>80 ensuring light quality. Available as Switched, 1-10V and DALI dimming options in 3000K 4000K 5000K colour temperature.

Features

- > Various of functions for options
- > High lumen output at 120LM/W UGR<19
- > CCT: 3000-4000-5000K
- > 5 years warranty



► CCT

Single Color
3000K
4000K
5000K
6000K

Tri-color
3000K
4000K
5000K
6000K

► Photometric Parameters

120 LM/W
CRI>80
SDCM <3
LM79
TM-21
ERP2.0

► Function

ON OFF
1-10V Dimming
DALI
MS
Emergency

► Electrical Parameters


AC 200-240V
PF ≈0.95
THD <15%
Flicker Free

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
PN400-22W-SN1-19F01-00	19W	typ.4320	typ.120	Y	L595 X W295 X H50	5.5kg	1pcs
PN400-41W-SN1-36F01-00	36W	typ.4320	typ.120	Y	L1195 X W295 X H50	8.5kg	1pcs



EVO Down Light DL100



Evo down light is new cost-effective backlit down light. It uses the plastic and steel bottom case.

The Evo down light offers 6 different dimensions and function options .

This cost effective down light makes more and more clients interested in it and use it on different applications.

Features

- > Cost-effective down light
- > Various of dimensions
- > Recessed Installation
- > Package : Standard or color box

CCT Single Color 3000K 4000K 5000K 6000K

Function   

Electrical Parameters



Photometric Parameters




Data Sheet

Order Code	Wattage	Lumen	LM/W	Flicker Free	Dimension (mm)	Cut-out(mm)	GW/CTN	QTY/CTN
DL100-09W-SN1-04F01-00	4W	typ.320	typ.80	Y	Ø90x25	Ø72	7.5kg	40pcs
DL100-12W-SN1-08F01-00	8W	typ.640	typ.80	Y	Ø120x25	Ø107	5.2kg	20pcs
DL100-17W-SN1-12F01-00	12W	typ.1200	typ.100	Y	Ø170x25	Ø156	4.6kg	10pcs
DL100-20W-SN1-15F01-00	15W	typ.1500	typ.100	Y	Ø200x25	Ø185	5.3kg	10pcs
DL100-34W-SN1-18F01-00	18W	typ.1980	typ.110	Y	Ø240x25	Ø225	6.6kg	10pcs
DL100-30W-SN1-22F01-00	22W	typ.2420	typ.110	Y	Ø300x25	Ø280	9.0kg	10pcs



Slim Down Light DL200



Slim Downlight is a round led panel light with an extra thin die-cast case. It uses the LGP as the light guide.

The 6 dimensions make the slim down widely used in various of different application.

Features

- > Full rage sizes are available
- > Recessed installation
- > Die casting aluminum case
- > Package : Standard or color box

CCT Single Color 3000K 4000K 5000K 6000K

Function   

Electrical Parameters



Photometric Parameters




Data Sheet

Order Code	Wattage	Lumen	LM/W	Flicker Free	Dimension (mm)	Cut-out(mm)	GW/CTN	QTY/CTN
DL200-09W-SN1-04F01-00	4W	typ.320	typ.80	Y	Ø88x25	Ø65	7.5kg	40pcs
DL200-12W-SN1-08F01-00	8W	typ.640	typ.80	Y	Ø120x25	Ø105	5.2kg	20pcs
DL200-17W-SN1-12F01-00	12W	typ.1200	typ.100	Y	Ø170x25	Ø155	4.6kg	10pcs
DL200-19W-SN1-15F01-00	15W	typ.1500	typ.100	Y	Ø190x25	Ø175	5.3kg	10pcs
DL200-24W-SN1-18F01-00	18W	typ.1980	typ.110	Y	Ø240x25	Ø225	6.6kg	10pcs
DL200-30W-SN1-22F01-00	22W	typ.2420	typ.110	Y	Ø300x25	Ø275	9.0kg	10pcs




Halo Down Light DL300



Halo Downlight, die casting aluminum housing design effectively reduce the UGR index. Interchangeable CCT with a slide switch is available.

Features

- > Die-cast housing as heat sink
- > Recessed installation
- > Full range dimension from 2.5 to 8 inches
- > Package : Standard or color box



Electrical Parameters



Photometric Parameters



Dimension: 2.5 / 4 / 5 / 6 / 8 inches




Data Sheet

Order Code	Wattage	Lumen	LM/W	Flicker Free	Dimension (mm)	Cut-out(mm)	GW/CTN	QTY/CTN
DL300-02W-SN1-05F01-00	5W	typ.450	typ.90	Y	Ø90x40	Ø80	5.6kg	20pcs
DL300-03W-SN1-09F01-00	9W	typ.1050	typ.120	Y	Ø120x40	Ø105	6.8kg	20pcs
DL300-04W-SN1-12F01-00	12W	typ.1440	typ.120	Y	Ø145x40	Ø130	8.0kg	20pcs
DL300-06W-SN1-20F01-00	20W	typ.2400	typ.120	Y	Ø175x40	Ø160	10.5kg	20pcs
DL300-08W-SN1-30F01-00	30W	typ.3600	typ.120	Y	Ø220x40	Ø205	7.5kg	10pcs




Halo Down Light DL400



Halo Downlight, die casting aluminum housing design effectively reduce the UGR index. Interchangeable CCT with slide switch is available.

Features

- > Die-cast housing as heat sink
- > Recessed instalation
- > Full range dimension from 2.5 to 8 inches
- > Package : Standard or color box



Electrical Parameters



Photometric Parameters



Dimension: 2.5 / 4 / 5 / 6 / 8 inches




Data Sheet

Order Code	Wattage	Lumen	LM/W	Flicker Free	Dimension (mm)	Cut-out(mm)	GW/CTN	QTY/CTN
DL400-02W-SN1-05F01-00	5W	typ.450	typ.90	Y	L90 X W90 X H40	80x80	6.0kg	20pcs
DL400-03W-SN1-09F01-00	9W	typ.1050	typ.120	Y	L120 X W120 X H40	105x105	7.6kg	20pcs
DL400-04W-SN1-12F01-00	12W	typ.1440	typ.120	Y	L145 X W145 X H40	130x130	9.2kg	20pcs
DL400-06W-SN1-20F01-00	20W	typ.2400	typ.120	Y	L170 X W70 X H40	160x160	11.5kg	20pcs
DL400-08W-SN1-30F01-00	30W	typ.3600	typ.120	Y	L220 X W220 X H40	205x205	8.9kg	10pcs



T8 LED Tube

TU08



The T8 LED tube is often used with office lighting and warehouse applications and can be used in both indirect and parabolic light fixtures. The T8 tube with high lumen efficacy 160lm/w can save you more money. It's the best replacement for the fluorescent lamp.

Features

- > TUV/CE/ROHS approval
- > Rotatable end cap
- > Up to 60% energy savings
- > 50,000 hours life span & 5 years warranty
- > Pink color for meat

CCT Single Color 3000K 4000K 5000K 6000K

Function ON OFF

Electrical Parameters

AC 200-240V	PF ≥0.95	THD <15%	Flicker Free
----------------	-------------	-------------	-----------------

Photometric Parameters

100/120 LM/W	140/160 LM/W	CRI>80 SDCM <5	LM79 TM-21	ERP2.0
-----------------	-----------------	----------------------	---------------	--------

Wiring

Single wiring	Double wiring
------------------	------------------


Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
TU08-02S-CN1-10F01-00	10W	typ.1600	typ.160	Y	L603 X D26	7.0kg	25pcs
TU08-03S-CN1-12F01-00	12W	typ.1920	typ.160	Y	L913 X D26	12.0kg	25pcs
TU08-04S-CN1-28F01-00	28W	typ.4480	typ.160	Y	L1212 X D26	12.5kg	25pcs
TU08-04S-CN1-22F01-00	22W	typ.3520	typ.160	Y	L1212 X D26	12.5kg	25pcs
TU08-05S-CN1-22F01-00	22W	typ.3520	typ.160	Y	L1513X D26	14.2kg	25pcs
TU08-06S-CN1-30F01-00	30W	typ.4800	typ.160	Y	L1813X D26	17.2kg	25pcs



T6 LED Tube

TU06



The T6 tube is the best replacement for the T5 fluorescent lamp. It is used with office lighting and warehouse applications and can be used in both indirect and parabolic light fixtures.

Features

- > TUV/CE/ROHS approval
- > Rotatable end cap
- > Special Design for G5 cap
- > Up to 60% energy savings & 50,000 hours life span
- > Pink color for meat

CCT Single Color 3000K 4000K 5000K 6000K

Function ON OFF

Electrical Parameters

AC 200-240V	PF ≥0.95	THD <15%	Flicker Free
----------------	-------------	-------------	-----------------

Photometric Parameters

100/120 LM/W	140/160 LM/W	CRI>80 SDCM <5	LM79 TM-21	ERP2.0
-----------------	-----------------	----------------------	---------------	--------

Wiring

Single wiring	Double wiring
------------------	------------------


Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
TU06-02S-CN1-10F01-00	10W	typ.1600	typ.160	Y	L549 X D22	12.5kg	50pcs
TU06-04S-CN1-18F01-00	18W	typ.2880	typ.160	Y	L1148 X D22	12.5kg	25pcs
TU06-05S-CN1-22F01-00	22W	typ.3520	typ.160	Y	L1449 X D22	14.5kg	25pcs
TU06-05S-CN1-25F01-00	25W	typ.4000	typ.160	Y	L1449 X D22	14.5kg	25pcs
TU06-06S-CN1-30F01-00	30W	typ.4800	typ.160	Y	L1749 X D22	18.9kg	25pcs



Cabinet Light

CB01



Cabinet lights were designed for use on cupboards, showcases, shopping malls.

Full plastic case and various of connectors make the cabinet light easy multiple link and easy installation.

- Features
- > Ideal for retro-fit of existing T4 and T5 fixtures
 - > Full set of connectors and accessories supplied
 - > Slimline profile for discreet installation
 - > Extruded plastic body
 - > 3 years warranty

CCT Single Color 3000K 4000K 5000K 6000K

Function

Electrical Parameters

AC 200-240V	PF ≥0.95	THD <15%	Flicker Free
----------------	-------------	-------------	-----------------

Photometric Parameters

100 LM/W	CRi>80 SDCM <5	LM79 TM-21
-------------	----------------------	---------------

Connector See below page
Accessories



Cabinet Light

Accessories



AC Input connector



Wire multiple connector



Wireless multiple connector



End cap



Installation clip



Installation clip


Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
CB01-02W-GN1-03F01-00	3W	typ.300	typ.100	N	L200 X W23 X H37	15kg	60pcs
CB01-03W-GN1-05F01-00	5W	typ.500	typ.100	N	L300 X W23 X H37	17kg	60pcs
CB01-05W-GN1-08F01-00	8W	typ.800	typ.100	N	L500 X W23 X H37	10kg	30pcs
CB01-09W-GN1-14F01-00	14W	typ.1400	typ.100	N	L900 X W23 X H37	13kg	30pcs
CB01-12W-GN1-16F01-00	16W	typ.1600	typ.100	N	L1200 X W23 X H37	16kg	30pcs



REVO UFO

HB100



With built-in driver, REVO-UFO is a cost-effective and compact high bay series. Dia.361mm heat sink guarantees good heat dissipation, All of the above features make this UFO were widely use on different industrial applications

Features

- > 130lm/w and 160lm/w
- > Full wattage:100W, 120W, 150W, 200W.
- > Intelligent control: microwave motion sensor, PIR sensor, CASAMBI wireless control

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
HB100-30B-DN1-1AF01-00	100W	typ.13000	typ.130	Y	D301 X H72	12kg	4pcs
HB100-30B-DN1-1BF01-00	120W	typ.15600	typ.130	Y	D301 X H72	12kg	4pcs
HB110-36B-DN1-1BF01-00	150W	typ.19500	typ.130	Y	D361 X H75	14kg	4pcs
HB110-36B-DN1-2AF01-00	200W	typ.26000	typ.130	Y	D361 X H75	14kg	4pcs



CCT Single Color 3000K 4000K 5000K 6000K

Function ON OFF 1-10V Dimming DALI MS On/Off Sensor Emergency

Electrical Parameters AC 100-277V PF ≥0.95 THD <15% Flicker Free

Photometric Parameters 130 LM/W 150 LM/W CRI>80 SDCM <5 LM79 TM-21 ERP2.0

IP/IK IP65 IK10

Installation Loop Hanging Hook Mounting Ceiling Mounting Bracket Mounting



Mounting Options



Sensor Function




INTRODUCTION

The ANT-5-4R is a motion sensor that dims lighting from high to low based on movement. This slim, low-profile sensor is designed for installation inside the bottom of a light fixture body.

The sensors use microwave sensing technology that reacts to changes in movement within the coverage area. Once the sensor stops detecting movement and the time delay elapses lights will go from high to low mode and eventually to an OFF position if it is desired. Sensors must directly "see" motion of a person or moving object to detect them, so careful consideration must be given to sensor luminaire placement and lens selection. Avoid placing the sensor where obstructions may block the sensor's line of sight.



Elite UFO HB200



Elite UFO is a new functional highbay light, Can use DIP switch wattage adjustable driver, Available on IP65 connector which make the Elite UFO easy for driver replace and AC wiring.


UP to 190 LM/W makes the Elite UFO deliver the reliable lumen output and lower light decay.

Features

- > Up to 190lm/W and die-cast case as heat sink
- > Wattage DIP switch adjustable (60%/80%/100%) & Stepless adjustable are available
- > Ripple Lens : 60°/ 90°/ 120°
- > Plug & Play sensor for MS /on/off/1-10V changing is available
- > Optional on IP65 connector for smart driver replace AC wiring
- > D-Mark tested for using on paper /wooden production
- > 5 years warranty

Data Sheet

Order Code	Rated Power	Wattage Adjustable	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
HB200-24B-DN1-75F01-00	75W	45W/60W/75W	Max.14250	typ.190	Y	D240X H155	3.5kg	1pcs
HB200-24B-DN1-1AF01-00	100W	60W/80W/100W	Max.19000	typ.190	Y	D240X H155	3.5kg	1pcs
HB210-28B-DN1-1BF01-00	150W	90W/120W/150W	Max.28500	typ.190	Y	D280X H163	4.5kg	1pcs
HB220-32B-DN1-2AF01-00	200W	120W/160W/200W	Max.38000	typ.190	Y	D320X H163	5.3kg	1pcs



Electrical Parameters



Photometric Parameters



Beam angle



IP/IK



Installation



Elite UFO Function Options



DIP Switch Wattage Adjustable
Stepless Wattage Adjustable



Smart IP65 Conny Connector,
easy to access to wiring to ensure
a quick and easy installation.

Smart IP65 Connector,
easy for driver replacement

Unique Die-casting
Fins heat sink



Plug in & Play MS Sensor, easy
to change from MS to 1-10V.


Ripple Lens PC Reflector:
60°/ 90°/ 120°





Mate UFO

HB400 | Honeycomb



Honeycomb mate UFO is an anti-glare design with UGR<22, The lumen efficiency up to 160lm/W.

Sleek anti glare design and die cast heat sink make the mate UFO widely use suitable on glare applications, Such as sports field, workshop, warehouse, etc.

Features

- > Up to 160lm/w
- > Anti-glare UGR<22
- > IP65 / IK10 for all industrial applications
- > Superior honeycomb-reflector-optic with 60°or 90°
- > L80/B10 @ 50.000h
- > D-Mark tested for using on paper / wooden production
- > Warranty: 5 years

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
HB400-30B-CN1-1AF01-00	100W	typ.16000	typ.160	Y	D300X H155	4.3kg	1pcs
HB400-30B-CN1-1BF01-00	150W	typ.24000	typ.160	Y	D300X H155	4.3kg	1pcs
HB410-35B-CN1-2AF01-00	200W	typ.32000	typ.160	Y	D350X H155	5.6kg	1pcs
HB410-35B-CN1-2BF01-00	240W	typ.38400	typ.160	Y	D350X H155	5.6kg	1pcs



CCT Single Color 3000K 4000K 5000K 6000K



Electrical Parameters



Photometric Parameters



Beam angle



IP/IK




Installation





Mate UFO

HB420 | Ripple Lens



Ripple lens mate UFO provide 60°/90°/120° beam angle, High lumen output up to 180LM/W.

The different beam angle deliver the high Lux output, And the die-cast heat sink helps on the heating dissipation.

All of the above features make this UFO were widely use on different industrial applications

Features

- > Up to 180lm/w
- > IP65 / IK10
- > Ripple lens optic with 60°/90°/120° beam angle;
- > D-Mark tested for the using on paper/wooden production
- > 5 years warranty

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
HB420-30B-LN1-1AF01-00	100W	typ.18000	typ.180	Y	D300X H155	4.3kg	1pcs
HB420-30B-LN1-1BF01-00	150W	typ.27000	typ.180	Y	D300X H155	4.3kg	1pcs
HB420-35B-LN1-2AF01-00	200W	typ.36000	typ.180	Y	D350X H155	5.6kg	1pcs
HB420-35B-LN1-2BF01-00	240W	typ.43200	typ.180	Y	D350X H155	5.6kg	1pcs



CCT Single Color 3000K 4000K 5000K 6000K

Function ON/OFF, 1-10V Dimming, DALI, MS, On/Off Sensor, Emergency


Electrical Parameters



Photometric Parameters




Beam angle



IP/IK




Installation



Mate UFO

HB430 | Glass Cover



Glass cover mate UFO has a high lighting transmission, The lumen output reach at 190LM/W, The die-cast heat sink helps on the heating dissipation.

All of the above features make this UFO were widely use on different industrial applications.

Features

- > Up to 190lm/w
- > Die cast heat sink for heating dissipation
- > IP65 / IK10
- > D-Mark tested for using on paper/wooden production
- > 5 years warranty

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
HB430-30B-LN1-1AF01-00	100W	typ.19000	typ.190	Y	D300X H155	4.3kg	1pcs
HB430-30B-LN1-1BF01-00	150W	typ.28500	typ.190	Y	D300X H155	4.3kg	1pcs
HB430-35B-LN1-2AF01-00	200W	typ.38000	typ.190	Y	D350X H155	5.6kg	1pcs
HB430-35B-LN1-2BF01-00	240W	typ.45600	typ.190	Y	D350X H155	5.6kg	1pcs



CCT Single Color 3000K 4000K 5000K 6000K

Function ON/OFF, 1-10V Dimming, DALI, MS, On/Off Sensor, Emergency

Electrical Parameters



Photometric Parameters



IP/IK




Installation





T-line

HB500



The symmetric honeycomb linear highbay is designed low glare applications up to 160LM/W, The symmetric honeycomb provide 60/90 degree beam angle .


The superior honeycomb -reflector-optic for low glare make this linear highbay be widely use on the industrial and commerial applications which need the low glare lighting emitting.

Features

- > Up to 160 lm/w
- > Die-cast case for excellent heat dissipation
- > Symmetric honeycomb for low glare
- > No UV or IR and completely mercury free
- > Various end cap colors available
- > L80/B10 @ 50.000h
- > 5 years warranty

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
HB500-02B-CN1-1AF01-00	100W	typ.16000	typ.160	Y	L623 X W138 X H73	5.9kg	1pcs
HB500-03B-CN1-1CF01-00	120W	typ.19200	typ.160	Y	L923 X W138 X H73	7.9kg	1pcs
HB500-03B-CN1-1BF01-00	150W	typ.24000	typ.160	Y	L923 X W138 X H73	7.9kg	1pcs
HB500-04B-CN1-2AF01-00	200W	typ.32000	typ.160	Y	L1223 X W138 X H73	10.0kg	1pcs



Electrical Parameters



Photometric Parameters



Beam angle




IP/IK





T-line

HB520




The asymmetric honeycomb linear highbay provide the 60X90 and 90x110 degree beamangle, The asymmetric angle make the highbay deliver a uniform lighting up to 160LM/W

The asymmetric honeycomb reflector also make the linear highbay UGR<22 low glare.

Features

- > Up to 160 lm/w
- > Die-cast case for excellent heat dissipation
- > Asymmetric honeycomb for low glare UGR<22
- > No UV or IR and completely mercury free
- > Various end cap colors available
- > L80/B10 @ 50.000h
- > 5 years warranty



Electrical Parameters



Photometric Parameters



Beam angle



IP/IK




Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
HB520-02B-CN1-1AF01-00	100W	typ.16000	typ.160	Y	L623 X W138 X H73	5.9kg	1pcs
HB520-03B-CN1-1CF01-00	120W	typ.19200	typ.160	Y	L923 X W138 X H73	7.9kg	1pcs
HB520-03B-CN1-1BF01-00	150W	typ.24000	typ.160	Y	L923 X W138 X H73	7.9kg	1pcs
HB520-04B-CN1-2AF01-00	200W	typ.32000	typ.160	Y	L1223 X W138 X H73	10.0kg	1pcs



T-line

HB540




The glass cover linear highbay provide frosted and clear version up to 180 LM/W

The cooling fins aluminum case assures the excellent heating dissipation.

Features

- > Frosted :170LM/W, Clear :180LM/W
- > Die-cast case for excellent heat dissipation
- > No UV or IR and completely mercury free
- > Various end cap colors available
- > L80/B10 @ 50.000h
- > 5 years warranty



Electrical Parameters



Photometric Parameters




IP/IK




Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
HB540-02B-CN1-1AF01-00	100W	typ.17000	typ.170	Y	L623 X W138 X H73	5.9kg	1pcs
HB540-03B-CN1-1CF01-00	120W	typ.20400	typ.170	Y	L923 X W138 X H73	7.9kg	1pcs
HB540-03B-CN1-1BF01-00	150W	typ.25500	typ.170	Y	L923 X W138 X H73	7.9kg	1pcs
HB540-04B-CN1-2AF01-00	200W	typ.34000	typ.170	Y	L1223 X W138 X H73	10.0kg	1pcs



Modular Highbay

HB600 | 3x100W-60CM




Modular highbay use the 60CM / 90CM / 120CM T-Line unit as the basic unit, Aluminum heat sink deliver the best heating dissipation which make the highbay offer a long life span and lower light decay

The special designed Honeycomb reflectors reduces glaring and provides various symmetric and asymmetric beam angle choices for all possible areas of applications.

Features

- > Superior honeycomb-reflector-optic for low glare
- > Asymmetric Honeycomb reflector for 60°90° degree
- > Glass cover up to 180 lm/w
- > Cooling-finings structure for excellent heat dissipation
- > L80/B10 @ 50.000h
- > 5 years warranty



Electrical Parameters



Photometric Parameters



Cover

Symmetric honeycomb
Asymmetric honeycomb
Glass cover

Beam angle



IP/IK




Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
HB600-02B-CN1-3AF01-00	300W	typ.48000	typ.160	Y	L624 X W438 X H83	15.6kg	1pcs
HB601-02B-CN1-3AF01-00	300W	typ.48000	typ.160	Y	L624 X W438 X H83	15.6kg	1pcs
HB620-02B-CN1-3AF01-00	300W	typ.51000	typ.170	Y	L624 X W438 X H83	15.6kg	1pcs
HB621-02B-CN1-3AF01-00	300W	typ.54000	typ.180	Y	L624 X W438 X H83	15.6kg	1pcs



Modular Highbay

HB602 | 3x150W-90CM




Modular highbay use the 60CM / 90CM / 120CM T-Line unit as the basic unit, Aluminum heat sink deliver the best heating dissipation which make the highbay offer a long life span and lower light decay

The special designed Honeycomb reflectors reduces glaring and provides various symmetric and asymmetric beam angle choices for all possible areas of applications.

Features

- > Superior honeycomb-reflector-optic for low glare
- > Asymmetric Honeycomb reflector for 60°90° degree
- > Glass cover up to 180 lm/w
- > Cooling-finings structure for excellent heat dissipation
- > L80/B10 @ 50.000h
- > 5 years warranty



Electrical Parameters



Photometric Parameters



Cover

Symmetric honeycomb
Asymmetric honeycomb
Glass cover

Beam angle




IP/IK




Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
HB602-03B-CN1-1BF01-00	450W	typ.72000	typ.160	Y	L924 X W438 X H83	19.5kg	1pcs
HB603-03B-CN1-1BF01-00	450W	typ.72000	typ.160	Y	L924 X W438 X H83	19.5kg	1pcs
HB623-03B-CN1-1BF01-00	450W	typ.76500	typ.170	Y	L924 X W438 X H83	19.5kg	1pcs
HB624-03B-CN1-1BF01-00	450W	typ.81000	typ.180	Y	L924 X W438 X H83	19.5kg	1pcs



Modular Highbay

HB604 | 3x200Wx120CM



Modular highbay use the 60CM / 90CM / 120CM T-Line unit as the basic unit, Aluminum heat sink deliver the best heating dissipation which make the highbay offer a long life span and lower light decay

The special designed Honeycomb reflectors reduces glaring and provides various symmetric and asymmetric beam angle choices for all possible areas of applications.

Features

- > Superior honeycomb-reflector-optic for low glare
- > Asymmetric Honeycomb reflector for 60°90° degree
- > Glass cover up to 180 lm/w
- > Cooling-finings structure for excellent heat dissipation
- > L80/B10 @ 50.000h
- > 5 years warranty



CCT Single Color 3000K 4000K 5000K 6000K Tri-color

Function ON OFF 1-10V Dimming DALI MS 0-10V Dimming Emergency

Electrical Parameters AC 100-277V PF ≥0.95 THD <15% Flicker Free

Photometric Parameters 140 LM/W 160 LM/W 180 LM/W CRI>80 SDCM <5 LM79 TM-21 ERP2.0

Cover Symmetric honeycomb Asymmetric honeycomb Glass cover


Beam angle 60° 90° 60°x110° 90°x110° 120° Symmetric Honeycomb Asymmetric Honeycomb Glass

IP/IK IP65 IK10

Data Sheet

Order Code	Rated Power	Lumen	LM/W	Flicker Free	Dimension (mm)	GW/CTN	QTY/CTN
HB604-04B-CN1-1BF01-00	600W	typ.96000	typ.160	Y	L1224 X W438 X H83	25.2kg	1pcs
HB605-04B-CN1-1BF01-00	600W	typ.96000	typ.160	Y	L1224 X W438 X H83	25.2kg	1pcs
HB625-04B-CN1-1BF01-00	600W	typ.102000	typ.170	Y	L1224 X W438 X H83	25.2kg	1pcs
HB626-04B-CN1-1BF01-00	600W	typ.108000	typ.180	Y	L1224 X W438 X H83	25.2kg	1pcs

Modular Highbay product categories



Contact details

IINNO Ltd

Unit 7, 8/F., Tower B,
83 King Lam Street,
Lai Chi Kok, Kowloon,
Hong Kong

Tel: +852 2134 9906

+86 (0)769 23010151/2

M: +86 13922905402

Email: sales@iinno-lighting.com

www.iinno-lighting.com

