


Commercial Track Lighting

Designing your lighting solutions





TL29A/C



TL29B/D




TL29E




TL29F

TL29 Track Light /Series/






TL29A Track light



TL29A driverless track light adopts high quality brand DOB led light source. Standard/honeycomb/shu er trims for optional

Materials of Housing : Aluminium

Materials of Optics : PC




Code	Watt	Size(AxBxCmm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
TL29A-20W	20W	Ø85x170x261	1560lm	0.55	12PCS
TL29A-30W	30W	Ø100x200x291	2550lm	0.79	12PCS
TL29A-40W	40W	Ø100x200x291	3400lm	0.79	12PCS

CCT — 2700K — 3000K — 4000K Finish — White — Black — Silver

Trim Accessories — Standard — Barn Door ACC-TL29-50 — Honeycomb Louver ACC-TL29-51 — Cross Louver ACC-TL29-52


TL29B Track light



TL29B track light adopts brand Citi en COB with CRI80 CRI90 CRI97 for options. rand Trodonic Driver available,also could be for Fresh Lighting with Citi en CRI95 Natruual Vivid COB.Standard/ honeycomb/shu er trims for optional

Materials of Housing : Aluminium

Materials of Optics : PC




Code	Watt	Size(AxBxCmm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
TL29B-12W	12W	Ø65x150x188	1200lm	0.52	12PCS
TL29B-25W	25W	Ø85x170x206	2750lm	0.75	12PCS
TL29B-35W	35W	Ø85x200x206	3675lm	0.79	12PCS
TL29B-42W	42W	Ø100x200x220	4410lm	1.05	12PCS

CCT — 2700K — 3000K — 4000K Finish — White — Black — Silver

Trim Accessories — Standard — Barn Door ACC-TL29-50 — Honeycomb Louver ACC-TL29-51 — Cross Louver ACC-TL29-52




TL29C Track light



TL29C track light adopts brand Citi en COB led chip with internal driver. Standard/honeycomb/shu er trims for optional

Materials of Housing : Aluminium

Materials of Optics : PC




Code	Watt	Size(AxBxCmm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
TL29C-12W	12W	Ø65x150x243	1200lm	0.47	12PCS
TL29C-25W	25W	Ø85x200x291	2750lm	0.68	12PCS
TL29C-35W	35W	Ø100x200x291	3675lm	0.79	12PCS

CCT ——— 2700K 3000K 4000K Finish ——— White Black Silver

Trim Accessories ——— Standard Barn Door ACC-TL29-50 Honeycomb Louver ACC-TL29-51 Cross Louver ACC-TL29-52


TL29D Track light



TL29D track light is minimalist design with external driver. It adopts high lumen SMD LED, anti glare PC lens to achieve great lighting distributio Tri-color with slide switch to reduce stock,standard/honeycomb/shu er trims for optional

Materials of Housing : Aluminium

Materials of Optics : PC




Code	Watt	Size(AxBxCmm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
TL29D-20W-C3	20W	Ø85x170x206	1800lm	0.75	12PCS
TL29D-30W-C3	30W	Ø85x200x206	2600lm	0.79	12PCS

CCT ——— 3000K 4000K 5700K Finish ——— White Black Silver

Trim Accessories ——— Standard Barn Door ACC-TL29-50 Honeycomb Louver ACC-TL29-51 Cross Louver ACC-TL29-52




TL29E Track light



TL29E is with integrated designed of driver and adapter Adopt brand Citi en COB led light source, high quality, reliable performance. CRI80 CRI90 CRI97 for options. tandard/honeycomb/shu er trims available.

Materials of Housing : Aluminium

Materials of Optics : PC




Code	Watt	Size(AxBxCxDmm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
TL29E-25W	25W	Ø85x170x258x198	2750lm	0.65	12PCS
TL29E-35W	35W	Ø85x200x288x198	3675lm	0.68	12PCS

CCT ——— 2700K 3000K 4000K Finish ——— White Black Silver

Trim Accessories ——— Standard Barn Door ACC-TL29-50 Honeycomb Louver ACC-TL29-51 Cross Louver ACC-TL29-52


TL29F Track light



TL29F adopts brand Citi en COB led light source, and external Tridonic DALI driver to ensure high quality, reliable performance. CRI80 CRI90 CRI97 for options. tandard/honeycomb/shu er trims available.

Materials of Housing : Aluminium

Materials of Optics : PC




Code	Watt	Size(AxBxCxDmm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
TL29F-25W	25W	Ø85x170x298x198	2610lm	0.90	12PCS
TL29F-35W	35W	Ø85x200x328x198	3490lm	0.95	12PCS
TL29F-42W	42W	Ø100x200x328x198	4110lm	1.20	12PCS

CCT ——— 2700K 3000K 4000K Finish ——— White Black Silver

Trim Accessories ——— Standard Barn Door ACC-TL29-50 Honeycomb Louver ACC-TL29-51 Cross Louver ACC-TL29-52




TL90 Track light



TL90 is a high-end track light with professional optical design. It adopts COB light source, special deep reflector or design achieves anti-glare effect (Type A UGR<10, Type B UGR<17). Module design provides an easily replacement with different optic parts: reflector or tempered glass with circle lighting spot, reflector or special PC lens with oval lighting spot. Compact structure with big power 40W/50W which meets a high brightness demand. Horizontally 358 degree, vertically 180 degree rotary. DALI dim available.

Materials of Housing : Die-casting Aluminium


Materials of Optics : Glass+Aluminium/ PC+Aluminium



Code	Watt	Size(AxBmm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
TL90-70-15W	15W	Ø70x214	1250lm	0.54	6PCS
TL90A-90-30W-A3	20W/25W/30W	Ø90x295	20W:2100lm/25W:2400lm/30W:2750lm	1.20	6PCS
TL90A-110-40W-A3	30W/35W/40W	Ø110x294.8	30W:3200lm/35W:3600lm/40W:3800lm	1.25	6PCS
TL90A-125-50W-A3	40W/45W/50W	Ø125x315.4	40W:4000lm/45W:4400lm/50W:4700lm	1.56	6PCS
TL90A-110-30W-DA	30W	Ø110x294.8	2600lm	1.25	6PCS
TL90A-125-40W-DA	40W	Ø125x315.4	3500lm	1.56	6PCS
TL90B-90-30W-A3	20W/25W/30W	Ø90x280	20W:2300lm/25W:2850lm/30W:3100lm	1.20	6PCS
TL90B-110-40W-A3	30W/35W/40W	Ø110x269.8	30W:3300lm/35W:3700lm/40W:4000lm	1.25	6PCS
TL90B-125-50W-A3	40W/45W/50W	Ø125x287.4	40W:4000lm/45W:4600lm/50W:5000lm	1.56	6PCS
TL90B-110-30W-DA	30W	Ø110x269.8	2900lm	1.25	6PCS
TL90B-125-40W-DA	40W	Ø125x287.4	3800lm	1.56	6PCS


CCT — 2700K — 3000K — 4000K — Finish — White — Black — Silver

INTERCHANGEABLE REFLECTOR AND DIFFUSER






TL69A Track light



TL69 series track light with focus adjustable design, special lens can have a fast beam angle change (Just press the lens). Adopt high lumen Citi en light source, two bracket design options, chan eable lighting orie tation with 350° in horizontal directio and 300° in vertical di ection

Materials of Housing : PC/Aluminium

Materials of Optics : PMMA




Code	Watt	Size(AxBmm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
TL69A-25W	25W	Ø96x298	2950lm	1.20	12PCS
TL69A-35W	35W	Ø96x298	3950lm	1.20	12PCS

CCT — 2700K — 3000K — 4000K

Finish — White — Black




TL69B Track light



TL69B track light is with special design with lens changeable 36°~60°by press . Adopt high lumen Citi en light source e ected 115lm/w. Black and white finish color for option

Materials of Housing : PC/Aluminium

Materials of Optics : PMMA




Code	Watt	Size(AxBmm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
TL69B-25W	25W	Ø96x298	2950lm	1.20	12PCS
TL69B-35W	35W	Ø96x298	3950lm	1.20	12PCS

CCT — 2700K — 3000K — 4000K

Finish — White — Black




TL57A Track light



TL57A led track light with built-in driver, it adopts brand Citizen COB chip. Secondary optics with lens and reflector make more uniform light.

Materials of Housing : Aluminium

Materials of Optics : PC




Code	Watt	Size(AxBxCmm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
TL57A-10W-D	10W	Ø65x127x223	1050lm	0.51	12PCS
TL57A-25W-D	25W	Ø80x157x254	2500lm	0.81	12PCS
TL57A-35W-D	35W	Ø100x167x259	3450lm	1.03	12PCS
TL57A-15W	15W	Ø65x127x223	1600lm	0.51	12PCS
TL57A-25W	25W	Ø80x157x254	2700lm	0.81	12PCS
TL57A-35W	35W	Ø100x167x259	3800lm	1.03	12PCS

CCT — 2700K — 3000K — 4000K — Finish — White — Black — Silver




TL58A Track light



TL58A LED track light with internal driver adopts CITIZEN chips with high quality LED source, CRI80/90/97 optional. Secondary optics with lens make more uniform light.

Materials of Housing : Aluminium

Materials of Optics : PC




Code	Watt	Size(AxBxCmm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
TL58A-15W	15W	Ø65x131x 227	1650lm	0.52	12PCS
TL58A-25W	25W	Ø80x152.5x249	2750lm	0.82	12PCS
TL58A-35W	35W	Ø100x167x259	3850lm	1.10	12PCS

CCT — 2700K — 3000K — 4000K — Finish — White — Black — Silver




TL02 Track light



TL02 LED track light with internal driver adopts CREE/ CITIZEN branded chips, providing adjustable lighting orientation with 360 degree in horizontal direction and 180 in vertical direction

Materials of Housing : Die-casting Aluminium

Materials of Optics : PC




Code	Watt	Size(AxBxCxDmm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
TL02-12W	12W	Ø75x104x220x126.5	1380lm	0.70	12PCS
TL02-25W	25W	Ø90x121x233x141	2500lm	1.17	12PCS
TL02-35W	35W	Ø110x131x234x161	3600lm	1.30	8PCS
TL02-45W	45W	Ø110x131x234x161	4380lm	1.30	8PCS

CCT ——— 2700K 3000K 4000K Finish ——— White Black Silver




TL127 Track light



TL127 track light using high-lumen COB chip, the design presents a contrast and harmonious appearance, multi beam Angle reflector, modular design, easy to replace. Track installation, suitable for clothing stores, hotels, exhibition rooms and other indoor commercial lighting

Materials of Housing : Aluminium

Materials of Optics : Aluminium




Code	Watt	Size(AxBmm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
TL127-86-16W	16W	Ø86x198	2200lm	0.44	12PCS
TL127-86-25W	25W	Ø86x198	3300lm	0.44	12PCS
TL127-97-25W	25W	Ø97x210	3300lm	0.56	12PCS
TL127-97-35W	35W	Ø97x210	4400lm	0.56	12PCS

CCT ——— 2700K 3000K 4000K Finish ——— White Black Nickel




TL25 Track light



TL25 LED track light with dimming button on the bottom of the track light adopts CITIZEN LED, adjustable lighting orientation with 360 degree in horizontal direction and 180 in vertical direction, 1-circuit adapter, 3-circuit adapter available for wide choice.

Materials of Housing : Aluminium

Materials of Optics : PC



Code	Watt	Size(AxBxCxDmm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
TL25-15W	15W	Ø68x83x170x102	1470lm	0.38	18PCS
TL25-25W	25W	Ø90x118.5x215x146	2600lm	0.68	12PCS
TL25-35W	35W	Ø105x128x215x161	3600lm	0.85	12PCS
TL25-45W	45W	Ø105x128x215x161	4410lm	0.85	12PCS


CCT — 2700K — 3000K — 4000K

Finish — White — Black

Dimming button (100% down to 5%)




TL25B Track light



TL25B LED track light adopts CITIZEN LED, adjustable lighting orientation with 360 degree in horizontal direction and 180 in vertical direction and 1-circuit adapter, 3-circuit adapter available for wide choice.

Materials of Housing : Aluminium

Materials of Optics : PC



Code	Watt	Size(AxBxCxDmm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
TL25B-25W	25W	Ø90x118x247x207	2600lm	0.75	12PCS
TL25B-35W	35W	Ø105x128x262x207	3600lm	0.92	12PCS
TL25B-45W	45W	Ø105x128x262x207	4410lm	0.92	12PCS


CCT — 2700K — 3000K — 4000K

Finish — White — Black — Silver



MODULAR Design


TL129 Track light



TL129 led track light is modular design with high lumen COB led, CRI80 and CRI90 both available, low glare with UGR<19, reflector or is replaceable with various beam angle 24°/36°/50°, CCT interchangeable, triac dim and dali dim both available.

Materials of Housing : Aluminium

Materials of Optics : PC/Aluminium



Code	Watt	Size(AxBmm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
TL129-65-10W	10W	Ø65x96	1250lm	0.39	24PCS
TL129-65-15W	15W	Ø65x96	1700lm	0.39	24PCS
TL129-85-20W	20W	Ø85x130	2300lm	0.72	12PCS
TL129-85-25W	25W	Ø85x130	2850lm	0.72	12PCS
TL129-85-27W-D	27W	Ø85x130	3100lm	0.74	12PCS
TL129-85-28W	28W	Ø85x130	3300lm	0.72	12PCS

CCT — 2700K — 3000K — 4000K

Finish — White — Black




Lighting source interchangeable

Reflector interchangeable

Honeycomb optional



TL120 Track light



TL120 is a track spotlight with versatility and a high degree of flexibility in terms of combination, adopts high CRI COB light source. It can be horizontally rotated up to 350 degrees and vertically tilted up to 180 degrees, allowing for versatile lighting angles and directions. CT Interchangeable is available. TL120A is dry damping design, TL120B adopts stepless zooming technology.

Materials of Housing : Die-casting Aluminium

Materials of Optics : Glass (TL120A)/ PC(TL120B)



Code	Watt	Size(AxBxCmm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
TL120A-32W-P2/D	32W	360x88.9x267	750lm	1.86	6PCS
TL120B-32W-P2/D	32W	263x92x170	3250lm	1.19	6PCS

CCT ——— 2700K ——— 3000K ——— 4000K

Finish ——— White ——— Black

DIY MODULE



TL120A

Optical-grade variable aperture design




Multi-layer dry damping design



Color



Projection



TL120B

ZOOM lens



Four-blade baffle



Stretch optics




360° manual rotation design





TL135 Track light



TL135 track light, intelligent induction color change design. It can automatically adjust the color temperature according to the environmental color change, changing the color according to the need to achieve a variety of decorative effects. Very suitable for home, office, exhibition, display etc

Materials of Housing : Aluminium

Materials of Optics : PC



Code	Watt	Size(AxBmm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
TL135-33W	33W	Ø100x294	1800lm	1.24	6PCS

CCT ——— 2700K ——— 3000K ——— 5100K

Finish ——— Black



TL135


2700K-5100K

Colour-Sensor

4000K Ra95


TL135

SUNLIGHT






TL56 Track light



TL56 track light with simple and elegant design, One track light with adjustable beam angle varies from 15° to 60°, creating a diversified and dramatic atmosphere. Lens optical design with even light output. Changeable lighting orientation with 350° in horizontal direction and 90° in vertical direction. Single CCT and interchangeable CCT available.

Materials of Housing : Aluminium

Materials of Optics : PC




Code	Watt	Size(AxBxCmm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
TL56-10W-D	10W	Ø65x234	960lm	0.69	12PCS
TL56-25W-D	25W	Ø80x260	2500lm	0.91	12PCS
TL56-30W-D	30W	Ø100x260	2800lm	1.29	12PCS
TL56-15W	15W	Ø65x234	1500lm	0.69	12PCS
TL56-25W	25W	Ø80x260	2500lm	0.91	12PCS
TL56-30W	30W	Ø100x265	3000lm	1.29	12PCS
TL56-25W-C3 NEW	25W	Ø80x260	2250lm	0.91	12PCS
TL56-30W-C3 NEW	30W	Ø100x260	2750lm	1.29	12PCS

CCT — 2700K — 3000K — 4000K

Finish — White — Black


TL17 Track light



TL17 LED tracklight, using advancing zooming technology, have a flexible beam angle from 10° to 60°. Flicker free LED driver. Dimmable for option

Materials of Housing : Aluminium

Materials of Optics : PC




Code	Watt	Size(AxBxCmm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
TL17-35W	35W	Ø100x207x301	1790~3720lm	1.53	6PCS

CCT — 2700K — 3000K — 4000K

Finish — White — Black — Silver




TL79 Track light



TL79 track light is an integrated design with internal driver and 3 circuit adapter. It is with interchangeable lens 15°/24°/36°/60° and Replaceable rings Black/White/Gold/Silver.

Materials of Housing : PC/Aluminium


Materials of Optics : PMMA



Code	Watt	Size(AxBxCxDmm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
TL79-10W	10W	Ø90x43x146x196	1250lm	0.44	12PCS
TL79-18W	18W	Ø90x43x146x196	2150lm	0.44	12PCS
TL79-25W	25W	Ø120x43x178x207	2950lm	0.61	12PCS
TL79-30W	30W	Ø120x43x178x207	3350lm	0.61	12PCS
TL79-13W-DA	13W	Ø90x43x146x265	1600lm	0.52	12PCS
TL79-20W-DA	20W	Ø90x43x146x265	2300lm	0.52	12PCS
TL79-25W-DA	25W	Ø120x43x176x260	2650lm	0.65	12PCS
TL79-30W-DA	30W	Ø120x43x178x260	3200lm	0.65	12PCS

CCT — 2700K — 3000K — 4000K — Trim — White — Black — Silver — Golden


TL40B Track light



TL40B led track light adopts Citi en chip which can create a diversified and d amatic tmosphere. Adjustable lighting orie tation with 350° in horizontal direction and 90° in vertical di ection will bring a fl xible exposure. 1-circuit and 3-circuit are all available.


Materials of Housing : Aluminium

Materials of Optics : PC




Code	Watt	Size(AxBxCmm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
TL40B-10W	10W	Ø54x162x236	1000lm	0.45	24PCS
TL40B-12W	12W	Ø54x162x236	1200lm	0.45	24PCS

CCT — 2700K — 3000K — 4000K — Finish — White — Black — Silver




TL121 Track light



TL121 Track light is adjustable design with horizontal rotation 355°, vertical rotation 18°. The polarized track avoids direct light from the light source and reduces the luminous area perceived by the outside world. The relatively small size can wash very wide shelves, with uniform illumination and wide irradiation angle.

Materials of Housing : Aluminium

Materials of Optics : PC




Code	Watt	Size(AxBxCmm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
TL121-35W	35W	310x118x50	3850lm	1.26	6PCS
TL121-40W	40W	310x118x50	4400lm	1.26	6PCS


CCT — 2700K — 3000K — 4000K

Finish — White — Black






TL49 Track light



TL49 LED linear track light with louver reflector design. It's widely used as additional lighting compared with traditional spot track light. Adopt 2835SMD chip, louver reflector or make it anti-glare, Adjustable lighting orientation with 350° in horizontal direction and 220° in vertical direction.

Materials of Housing : Aluminium

Materials of Optics : PC+ABS




Code	Watt	Size(AxBxCxDmm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
TL49-15W	15W	319.5x42x195.5x70	1400lm	0.74	12PCS
TL49-30W	30W	424.5x42x195.5x70	2750lm	0.92	12PCS
TL49-37W	37W	529.5x42x195.5x70	3400lm	1.15	12PCS
TL49-45W	45W	529.5x42x195.5x70	3850lm	1.15	12PCS

CCT — 3000K — 4000K — 5700K Finish — White — Black — Silver



TL110 Track light



TL110 is a compact and exquisite track light. It adopts high lumen branded COB light source, special texture designed lens lowered glare to create a comfortable visual experience. Horizontally and vertically 350 degree rotation can be freely adjusted.

Materials of Housing : Aluminium


Materials of Optics : PMMA



Code	Watt	Size(AxBxCmm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
TL110-20W	20W	158x108x74	2350lm	0.63	12PCS
TL110-30W	30W	250x108x74	3400lm	0.67	12PCS


CCT — 2700K — 3000K — 4000K Finish — White — Black — Silver

TL151A Track light



TL151A is linear track light with SMD design, lens design with symmetric beam and asymmetric beam. High lumen efficiency up to 180lm/W. It is integral driver design. Splicing is available.


Materials of Housing : Aluminium
Materials of Optics : PC



Code	Watt	Size(AxBmm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
TL151A-600-30W-A4	20W/22W/26W/30W	605.8x79.5x61.5	5400lm	0.98	6PCS
TL151A-1200-60W-A4	39W/46W/53W/60W	1205.8x79.5x61.5	11000lm	1.95	4PCS
TL151A-1500-75W-A4	51W/59W/67W/75W	1505.8x79.5x61.5	13600lm	2.25	2PCS
TL151A-1500-100W-A4	70W/80W/90W/100W	1505.8x79.5x61.5	17500lm	2.25	2PCS


CCT ——— 2700K 3000K 4000K Finish ——— White Black

TL151B Track light



TL151B linear track light is SMD design, opal diffuse with symmetric beam. High lumen efficiency up to 180lm/W. It is integral driver design. Splicing is available.


Materials of Housing : Aluminium
Materials of Optics : PC



Code	Watt	Size(AxBmm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
TL151B-600-30W-A4	20W/22W/26W/30W	605.4x78x75	5050lm	0.94	6PCS
TL151B-1200-60W-A4	39W/46W/53W/60W	1205.4x78x75	10900lm	1.95	4PCS
TL151B-1500-75W-A4	51W/59W/67W/75W	1505.4x78x75	13100lm	2.25	2PCS
TL151B-1500-100W-A4	70W/80W/90W/100W	1505.4x78x75	17400lm	2.25	2PCS

CCT ——— 2700K 3000K 4000K Finish ——— White Black


TL50/B Track light



TL50 LED linear track light is a concise design with internal flicker free led driver. Adopting high lumen efficient SMD LED. Interchangeable CCT with slide switch is available.

Materials of Housing : Aluminium


Materials of Optics : PC



Code	Watt	Size(AxBxCxDmm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
TL50/B-10W	10W	650x32.5x52x436	1000lm	0.43	12PCS
TL50/B-16W	16W	650x32.5x52x436	1560lm	0.45	12PCS
TL50/B-25W	25W	1212x32.5x52x496	2550lm	0.76	12PCS
TL50/B-30W	30W	1212x32.5x52x496	3000lm	0.76	12PCS
TL50/B-30W	30W	1493x32.5x52x496	3000lm	0.92	12PCS

CCT — 3000K — 4000K — 5700K — Finish — White — Black — Silver


TL109 Track light



TL109 track light with both high lumen efficiency and low UGR. It adopts super high lumen SMD light source, combine with honeycomb optic reflector to reach a low UGR<19. Standard European 3 circuits track and multiple beam angles for options.

Materials of Housing : Aluminium

Materials of Optics : PC




Code	Watt	Size(AxBxCmm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
TL109-52W	52W	435x123x96	7000lm	1.62	6PCS

CCT — 3000K — 4000K — 5700K — Finish — White — Black



TL111 Track light



TL111 LED track light with Osram brand driver is specifically designed for supermarket aisles. Type A with an adapter at the side while type B with adapter at the back and can do 350 degree rotary. European standard three-circuit track system is suitable. High lumen efficient 130-140lm/W is available.

Materials of Housing : Aluminium


Materials of Optics : PMMA




Code	Watt	Size(AxBxCmm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
TL111A-50W	50W	670x190x80	7040lm	2.50	6PCS
TL111A-60W	60W	670x190x80	8250lm	2.50	6PCS
TL111A-80W	80W	670x190x80	10480lm	2.50	6PCS
TL111B-50W	50W	582x190x116	7040lm	2.50	6PCS
TL111B-60W	60W	582x190x116	8250lm	2.50	6PCS
TL111B-80W	80W	582x190x116	10480lm	2.50	6PCS

CCT — 3000K — 4000K — 5700K

Finish — White — Black



TL112 Track light



TL112 a new seamless linear track lighting system, which has thin body, light weight and compact structure, suitable for European standard three-circuit track system. Multiple PMMA lens optics 30°, 60°, 90°, double asymmetric 20° for options

Materials of Housing : Aluminium



Materials of Optics : PMMA




Code	Watt	Size(AxBxCmm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
TL112-40W	40W	1152x80x85	5100lm	2.17	6PCS
TL112-60W	60W	1152x80x85	7150lm	2.17	6PCS

CCT — 3000K — 4000K — 5700K

Finish — White — Black




TL113 Track light



TL113 a new seamless linear track lighting system with Osram brand driver, which has thin body, light weight and compact structure, suitable for European standard three-circuit track system. Optic design combines with diffuse and reflector, which make more uniform light output.

Materials of Housing : Aluminium

Materials of Optics : PC




Code	Watt	Size(AxBxCmm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
TL113-47W	47W	1142x60x98	6300lm	2.05	6PCS
TL113-63W	63W	1142x60x98	8550lm	2.05	6PCS

CCT — 3000K — 4000K — 5700K

Finish — White — Black


TL114 Track light



TL114 is designed specifically for supermarket aisles, shelves, corridors etc. The light source is divided into left and right parts, which can be rotated upwards by 90°. The unique structural design allows the product to fit different aisle widths and installation heights with high flexibility. A great compatibility with European standard 3-circuit track and convenient for group control.

Materials of Housing : Aluminium

Materials of Optics : PC




Code	Watt	Size(AxBxCmm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
TL114-57W	57W	416x135x60	7100lm	1.2	6PCS

CCT — 3000K — 4000K — 5700K

Finish — White — Black

TL115 Track light



TL115 is a two-wing bionic design and has a unique rectangular light distribution that guides users' eyes to the shelf. At the same time, the illumination on the ground will not be too high, which can greatly improve the utilization rate of light and reduce energy consumption. The wings can be tilted downward by 30°, which is convenient to adjust the beam angle and meet the requirements of different aisle widths and installation heights.

Materials of Housing : Aluminium

Materials of Optics : PC





Code	Watt	Size(AxBxCmm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
TL115-57W	57W	388x218x70	5500lm	1.52	6PCS

CCT — 3000K — 4000K — 5700K


Finish — White — Black

Angel's Wings

Multiple beam angle options:





• Tilted downward by 30°





Safety lock

Track System






3 Circuits Track System




Model No.	Track length	Shell Material	Colour	Package
Pro-0410-W / Pro-0410-S / Pro-0410-B	1M track actual one meter.(100cm)	Aluminium Extrusion	White ☐ Silver ☐ Black ☐	1 / 12
Pro-0415-W / Pro-0415-S / Pro-0415-B	1.5M track actual one meter. (150cm)	Aluminium Extrusion	White ☐ Silver ☐ Black ☐	1 / 12
Pro-0420-W / Pro-0420-S / Pro-0420-B	2M track actual one meter.(200cm)	Aluminium Extrusion	White ☐ Silver ☐ Black ☐	1 / 12
Pro-0430-W / Pro-0430-S / Pro-0430-B	3M track actual one meter.(300cm)	Aluminium Extrusion	White ☐ Silver ☐ Black ☐	1 / 8
Pro-04400-W / Pro-04000-S / Pro-04000-B	4M track actual one meter.(400cm)	Aluminium Extrusion	White ☐ Silver ☐ Black ☐	1 / 6

Live-End Connector



Model No.	Package	Colour
Pro-0431 L-W	1 / 150	White ☐
Pro-0431 L-S	1 / 150	Silver ☐
Pro-0431 L-B	1 / 150	Black ☐

Live-End Connector




Model No.	Package	Colour
Pro-0431 R-W	1 / 150	White ☐
Pro-0431 R-S	1 / 150	Silver ☐
Pro-0431 R-B	1 / 150	Black ☐

Mini Joiner



Model No.	Package	Colour
Pro-0433-W	1 / 400	White ☐
Pro-0433-S	1 / 400	Silver ☐
Pro-0433-B	1 / 400	Black ☐

Mini Joiner(Insulation)




Model No.	Package	Colour
Pro-0433A-W	1 / 150	White ☐
Pro-0433A-S	1 / 150	Silver ☐
Pro-0433A-B	1 / 150	Black ☐

End Cap




Model No.	Package	Colour
Pro-0432-W	1 / 500	White ☐
Pro-0432-S	1 / 500	Silver ☐
Pro-0432-B	1 / 500	Black ☐

Mini Joiner(Insulation)



Model No.	Package	Colour
Pro-0434-W	1 / 150	White ☐
Pro-0434-S	1 / 150	Silver ☐
Pro-0434-B	1 / 150	Black ☐

Twisted "L" Connector




Model No.	Package	Colour
Pro-0438-W	1 / 154	White □
Pro-0438-S	1 / 154	Silver ■
Pro-0438-B	1 / 154	Black ■

"+" Connector




Model No.	Package	Colour
Pro-0437-W	1 / 60	White □
Pro-0437-S	1 / 60	Silver ■
Pro-0437-B	1 / 60	Black ■

Ceiling mount, EZCLIK suspension kit with ROD




Model No.	Package	Colour
Pro-EZ0447-W	1 / 200	White □
Pro-EZ0447-S	1 / 200	Silver ■
Pro-EZ0447-B	1 / 200	Black ■

Ceiling mount, EZCLIK suspension kit with wire




Model No.	Package	Colour
Pro-EZ0448-W	1 / 200	White □
Pro-EZ0448-S	1 / 200	Silver ■
Pro-EZ0448-B	1 / 200	Black ■

Flexible Connector




Model No.	Package	Colour
Pro-0439-W	1 / 119	White □
Pro-0439-S	1 / 119	Silver ■
Pro-0439-B	1 / 119	Black ■

Adjustable "L" Connector



Model No.	Package	Colour
Pro-0435-W	1 / 119	White □
Pro-0435-S	1 / 119	Silver ■
Pro-0435-B	1 / 119	Black ■


T-Bar, EZCLIK mounting kit




Model No.	Package	Colour
Pro-M146T-W	1 / 500	White □
Pro-M146T-S	1 / 500	Silver ■
Pro-M146T-B	1 / 500	Black ■

Suspension Mounting Kits Manual


1) Adjust the EZCLICK Mounting Kit's Direction, put it vertical into the T-Bar ceiling, and then rotate right and fix as picture shows).



2) Adjust the EZCLICK Mounting Kit's Direction, put the track vertical into the EZCLICK Mounting Kit, rotate left and fix (the picture shows).




Twisted "T" Connector(Left)




Model No.	Package	Colour
Pro-M436L-W	1 / 84	White □
Pro-M436L-S	1 / 84	Silver ■
Pro-M436L-B	1 / 84	Black ■

Twisted "T" Connector(Right)




Model No.	Package	Colour
Pro-M436R-W	1 / 84	White □
Pro-M436R-S	1 / 84	Silver ■
Pro-M436R-B	1 / 84	Black ■

Ceiling Mount Reinforcement Plate with suspension wire




Model No.	Package	Colour
Pro-M147-W	1 / 200	White ☐
Pro-M147-S	1 / 200	Silver ☐
Pro-M147-B	1 / 200	Black ☐

Ceiling Mount Reinforcement Plate with suspension rod



Model No.	Package	Colour
Pro-M148-W	1 / 200	White ☐
Pro-M148-S	1 / 200	Silver ☐
Pro-M148-B	1 / 200	Black ☐

T-Bar, EZCLIK with Reinforcement Plate



Model No.	Package	Colour
Pro-M149-W	1 / 200	White ☐
Pro-M149-S	1 / 200	Silver ☐
Pro-M149-B	1 / 200	Black ☐


Suspension Hook




Model No.	Package	Colour
Pro-M142-W	1 / 500	White ☐
Pro-M142-S	1 / 500	Silver ☐
Pro-M142-B	1 / 500	Black ☐

Suspension Mounting Kits Manual

1) Put the Track into the EZCLICK Mounting Kits Parallely (As picture shows).




2) Release the start valve, press and get the wire rope through the EZCLICK Mounting Kit, rotate right the start valve and lock the wire rope (like picture shows).




Suspension Mounting Kits Manual

1) Put the Track into the EZCLICK Kit Parallely (As picture shows).




2) Rotate right the EZCLICK Kit and fix it on the rod.




Suspension Mounting Kits Manual

1) Put the Track into the EZCLICK Mounting Kits parallelly (As picture shows).



2) Adjust the EZCLICK Mounting Kit's direction, put the track vertically into the EZCLICK Mounting Kit, rotate right and fix (like picture shows).



Mechanical Adaptor




Model No.	Package	Colour
Pro-0449-W	1 / 100	White ☐
Pro-0449-S	1 / 100	Silver ☐
Pro-0449-B	1 / 100	Black ☐



Suspension kit



Model No.	Package	Colour
Pro-04SK-W	1 / 100	White ☐
Pro-04SK-S	1 / 100	Silver ☐
Pro-04SK-B	1 / 100	Black ☐



3 Circuits Recessed Track System



Model No.	Track length	Shell Material	Colour			Package
Pro-R410-W / Pro-R410-S / Pro-R410-B	1M track actual one meter.(100cm)	Aluminium Extrusion	White ☐	Silver ☐	Black ☐	1 / 9
Pro-R415-W / Pro-R415-S / Pro-R415-B	1.5M track actual one meter. (150cm)	Aluminium Extrusion	White ☐	Silver ☐	Black ☐	1 / 9
Pro-R420-W / Pro-R420-S / Pro-R420-B	2M track actual one meter.(200cm)	Aluminium Extrusion	White ☐	Silver ☐	Black ☐	1 / 9
Pro-R430-W / Pro-R430-S / Pro-R430-B	3M track actual one meter.(300cm)	Aluminium Extrusion	White ☐	Silver ☐	Black ☐	1 / 6
Pro-R4400-W / Pro-R4400-S / Pro-R4400-B	4M track actual one meter.(400cm)	Aluminium Extrusion	White ☐	Silver ☐	Black ☐	1 / 6

Live-end Connector Cover



Model No.	Package	Colour
Pro-R431-W	1 / 500	White ☐
Pro-R431-S	1 / 500	Silver ☐
Pro-R431-B	1 / 500	Black ☐

Live-End Connector



Model No.	Package	Colour
Pro-R434-W	1 / 400	White ☐
Pro-R434-S	1 / 400	Silver ☐
Pro-R434-B	1 / 400	Black ☐

Mini Joiner



Model No.	Package	Colour
Pro-R435-W	1 / 400	White ☐
Pro-R435-S	1 / 400	Silver ☐
Pro-R435-B	1 / 400	Black ☐

Mini Joiner(insulation)




Model No.	Package	Colour
Pro-R436-W	1 / 400	White ☐
Pro-R436-S	1 / 400	Silver ☐
Pro-R436-B	1 / 400	Black ☐


End Cap



Model No.	Package	Colour
Pro-R437-W	1 / 400	White ☐
Pro-R437-S	1 / 400	Silver ☐
Pro-R437-B	1 / 400	Black ☐






Single Circuit Track System 3 Wires




Model No.	Track length	Shell Material	Colour			Package
Pro-0310A	1M track with double end cap.(100cm)	Aluminium Extrusion	White	Silver	Black	1 / 12
Pro-0320A	2M track with double end cap.(200cm)	Aluminium Extrusion	White	Silver	Black	1 / 12
Pro-0330A	3M track with double end cap.(300cm)	Aluminium Extrusion	White	Silver	Black	1 / 9
Pro-03400A	4M track with double end cap.(400cm)	Aluminium Extrusion	White	Silver	Black	1 / 9
Pro-0302A	2'track with double end cap actual length24"	Aluminium Extrusion	White	Silver	Black	1 / 12
Pro-0304A	4'track with double end cap actual length48"	Aluminium Extrusion	White	Silver	Black	1 / 12
Pro-0306A	6'track with double end cap actual length72"	Aluminium Extrusion	White	Silver	Black	1 / 12
Pro-0308A	8'track with double end cap actual length96"	Aluminium Extrusion	White	Silver	Black	1 / 12
Pro-0310B	1M track with live end & end cap.(100cm)	Aluminium Extrusion	White	Silver	Black	1 / 12
Pro-0320B	2M track with live end & end cap.(200cm)	Aluminium Extrusion	White	Silver	Black	1 / 12
Pro-0330B	3M track with live end & end cap.(300cm)	Aluminium Extrusion	White	Silver	Black	1 / 9
Pro-03400B	4M track with live end & end cap.(400cm)	Aluminium Extrusion	White	Silver	Black	1 / 9
Pro-0302B	2'track with live end and end cap actual length24"	Aluminium Extrusion	White	Silver	Black	1 / 12
Pro-0304B	4'track with live end and end cap actual length48"	Aluminium Extrusion	White	Silver	Black	1 / 12
Pro-0306B	6'track with live end and end cap actual length72"	Aluminium Extrusion	White	Silver	Black	1 / 12
Pro-0308B	8'track with live end and end cap actual length96"	Aluminium Extrusion	White	Silver	Black	1 / 12
Pro-0310C	1M track with live end & end cap.(100cm)	Aluminium Extrusion	White	Silver	Black	1 / 12
Pro-0320C	2M track with live end & end cap.(200cm)	Aluminium Extrusion	White	Silver	Black	1 / 12
Pro-0330C	3M track with live end & end cap.(300cm)	Aluminium Extrusion	White	Silver	Black	1 / 9
Pro-03400C	4M track with live end & end cap.(400cm)	Aluminium Extrusion	White	Silver	Black	1 / 9
Pro-0302C	2'track with live end and end cap actual length24"	Aluminium Extrusion	White	Silver	Black	1 / 12
Pro-0304C	4'track with live end and end cap actual length48"	Aluminium Extrusion	White	Silver	Black	1 / 12
Pro-0306C	6'track with live end and end cap actual length72"	Aluminium Extrusion	White	Silver	Black	1 / 12
Pro-0308C	8'track with live end and end cap actual length96"	Aluminium Extrusion	White	Silver	Black	1 / 12

Single Circuit Recessed 3 Wires





Model No.	Track length	Shell Material	Colour			Package
Pro-R310A	1M track with double end cap.(100cm)	Aluminium Extrusion	White	Silver	Black	1 / 12
Pro-R320A	2M track with double end cap.(200cm)	Aluminium Extrusion	White	Silver	Black	1 / 12
Pro-R330A	3M track with double end cap.(300cm)	Aluminium Extrusion	White	Silver	Black	1 / 12
Pro-R3400A	4M track with double end cap.(400cm)	Aluminium Extrusion	White	Silver	Black	1 / 9
Pro-R302A	2'track with double end cap actual length24"	Aluminium Extrusion	White	Silver	Black	1 / 12
Pro-R304A	4'track with double end cap actual length48"	Aluminium Extrusion	White	Silver	Black	1 / 12
Pro-R306A	6'track with double end cap actual length72"	Aluminium Extrusion	White	Silver	Black	1 / 12
Pro-R308A	8'track with double end cap actual length96"	Aluminium Extrusion	White	Silver	Black	1 / 12
Pro-R310B	1M track with live end & end cap.(100cm)	Aluminium Extrusion	White	Silver	Black	1 / 12
Pro-R320B	2M track with live end & end cap.(200cm)	Aluminium Extrusion	White	Silver	Black	1 / 12
Pro-R330B	3M track with live end & end cap.(300cm)	Aluminium Extrusion	White	Silver	Black	1 / 12
Pro-R3400B	4M track with live end & end cap.(400cm)	Aluminium Extrusion	White	Silver	Black	1 / 9
Pro-R302B	2'track with live end and end cap actual length24"	Aluminium Extrusion	White	Silver	Black	1 / 12
Pro-R304B	4'track with live end and end cap actual length48"	Aluminium Extrusion	White	Silver	Black	1 / 12
Pro-R306B	6'track with live end and end cap actual length72"	Aluminium Extrusion	White	Silver	Black	1 / 12
Pro-R308B	8'track with live end and end cap actual length96"	Aluminium Extrusion	White	Silver	Black	1 / 12



Single Circuit Track System

2 Wires






Model No.	Track length	Shell Material	Colour
Pro-L210-W	1M / 1.5M / 2M / 3M track actual one meter. (100cm / 150cm / 200cm / 300cm)	Aluminium Extrusion	White ☐ Silver ☐ Black ☐



Model No.	Track length	Shell Material	Colour
Pro-RL210-W	1M / 1.5M / 2M / 3M track actual one meter. (100cm / 150cm / 200cm / 300cm)	Aluminium Extrusion	White ☐ Silver ☐ Black ☐

3 Circuit Recessed

6Wires



Model No.	Track length	Shell Material	Colour	Package
Pro-R610	1000(mm)	Aluminium Extrusion	White ☐ Silver ☐ Black ☐	1 / 9
Pro-R620	2000(mm)	Aluminium Extrusion	White ☐ Silver ☐ Black ☐	1 / 9
Pro-R630	3000(mm)	Aluminium Extrusion	White ☐ Silver ☐ Black ☐	1 / 6
Pro-R6400	4000(mm)	Aluminium Extrusion	White ☐ Silver ☐ Black ☐	1 / 4

Contact details

IINNO Ltd

Unit 7, 8/F., Tower B,
83 King Lam Street,
Lai Chi Kok, Kowloon,
Hong Kong

Tel: +852 2134 9906

+86 (0)769 23010151/2

M: +86 13922905402

Email: sales@iinno-lighting.com

www.iinno-lighting.com

